



TX-MOVE

742163.004.76 | Surface mounted projector



Surface mounted projectors
4051859755722
L 569, B 119, H 75

Track on ceiling
silver, matt (approx. RAL 9006)



Multifunctional surface-mounted spotlight for area lighting. Very flat design. Housing: sheet steel, powder-coated. Rotation range: 356°. Swivel range: 90°. Consistent alignment possible with visible tilt scale. High-efficiency LED units with optimum light control thanks to clear plastic (PC) lens optics. Spezielle Mikrostrukturen reduzieren Gelbsaum. Asymmetrical light distribution. With adapter for RZB 3-circuit DALI tracks. Suitable for Track on ceiling. MultiLumen: Luminous flux adjustable in 3 steps. Factory setting is the highest luminous flux. Environmentally friendly and resource-saving due to replaceable and recyclable components.

Product specifications

Length L	569 mm
Width B	119 mm
Height H	75 mm
Weight	2.05 kg
Light source	LED
Colour temperature	3000 K
Rated luminous flux	5500 lm 7400 lm 9050lm
System power	41 W 57 W 73W
System efficiency	124 lm/W 130 lm/W 134lm/W
Glare evaluation UGR (4H 8H)	26,4 27,4 28,1
Beam angle	73°/100°
Rated life	50000 h (L80/B10)
Colour rendering index (CRI)	80
Colour tolerance	3
Photobiological safety according to EN 62471	Risk group 1
Driver	Electronic ballast, dimmable
Control	DALI
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	8
Luminaires on B16A fuse	13
Luminaires on C10A fuse	13
Luminaires on C16A fuse	21
Inrush current / Inrush current duration	53 A / 215 µs
CIE Flux Code / CEN Flux Code	64 90 98 100 100
Type of protection	IP 20
Protection class	I
Filament test	850 °C
Impact resistance	IK04
Ambient temperature	5 °C ... + 25 °C
Conformity mark	CE