



CoreLine Trunking Gen2

LL212X 7x1.5 BC

LL212X | Coreline Trunking Gen2

CoreLine Trunking Gen2 is a light-line system that is designed for simplicity. It comes in a choice of lengths, flux packages and beam shapes to suit every project and application. Easy to use and integrate with spots and sensors, CoreLine Trunking Gen2 provides consistent, high-quality lighting with added protection against accidental water ingress. The innovative system is also easy to assemble and install for faster retrofits and refurbishments.

Product data

General Information		Material	
Accessory color	White		Steel
Product family code	LL212X [Coreline Trunking Gen2]	Approval and Application	
Value ladder	Value	Ingress protection code	IP20 [Finger-protected]
		Mech. impact protection code	IK02 [0.2 J standard]
		Protection class IEC	Safety class I
Operating and Electrical		Product Data	
Input Voltage	220 to 240 V	Full product code	871951410840000
Line Frequency	50 to 60 Hz	Order product name	LL212X 7x1.5 BC
Input Frequency	50 to 60 Hz	Order code	910925867583
		Numerator - Quantity Per Pack	1
Mechanical and Housing		Numerator - Packs per outer box	1
Overall length	1,130 mm	Material number (12NC)	910925867583
Overall width	80 mm	Full product name	LL212X 7x1.5 BC
Overall height	50 mm	EAN/UPC - Case	8719514108400
Dimensions (Height x Width x Depth)	50 x 80 x 1130 mm		

Dimensional drawing

