

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** PHILIPS

**Supplier's address:** Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

**Model identifier:** 8719514390089

## Type of light source:

|   |     |                                 |      |
|---|-----|---------------------------------|------|
| Lighting technology used:                           | HL  | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | R7S |                                 |      |
| Mains or non-mains:                                 | MLS | Connected light source (CLS):   | No   |
| Colour-tuneable light source:                       | No  | Envelope:                       | -    |
| High luminance light source:                        | No  |                                 |      |
| Anti-glare shield:                                  | No  | Dimmable:                       | Yes  |

## Product parameters

| Parameter  | Value                  | Parameter  | Value                  |    |
|--|------------------------|--|------------------------|----|
| <b>General product parameters:</b>   |                        |  |                        |    |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer  | 90                     | Energy efficiency class  | G                      |    |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 1 584 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000                  |    |
| On-mode power ( $P_{on}$ ), expressed in W   | 90,0                   | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal   | 0,00                   |    |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal  | -                      | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 100                    |    |
| Outer dimensions without   | Height                 | Spectral power distribution in the   | See image in last page |    |
|  | Width                  |  |                        | 78 |
|  | Depth                  |  |                        | 11 |

|   |   |                                      |                |
|---|---|--------------------------------------|----------------|
| separate control gear, lighting control parts and non-lighting control parts, if any (millimetre) |   | range 250 nm to 800 nm, at full-load |                |
| Claim of equivalent power <sup>(a)</sup>  | - | If yes, equivalent power (W)         | -              |
|   |   | Chromaticity coordinates (x and y)   | 0,440<br>0,403 |

(a) '-': not applicable;

(b) '-': not applicable;

