

# MADERA ALTUS LED EVO 900X900MM 4650LM PLX II IP41 WHITE 830 (50W)

DETAILED CARD



## TECHNICAL PARAMETERS

|                            |             |
|----------------------------|-------------|
| Index:                     | 703836      |
| Ingress protection:        | IP41        |
| Nominal power [W]:         | 50          |
| Luminous flux [lm]*:       | 4650        |
| Colour rendering index:    | >80         |
| SDCM:                      | ≤ 3         |
| Energy efficiency class:   | F           |
| Colour of the body:        | white       |
| Dimensions (H/W/T/S) [mm]: | 900/900/120 |

## CHARACTERISTICS

Suspended, square LED fitting with very high luminous flux, made of steel sheet, powder-coated grey, white, black. equipped with energy-saving light source LED-GO!. Opal PMMA diffuser ensures even light distribution and no glare effect.

## APPLICATION

Suspended luminaire intended for indoor use in offices or common rooms. Suitable as a general light source in representative rooms.

# MADERA ALTUS LED EVO 900X900MM 4650LM PLX II IP41

## WHITE 830 (50W)

DETAILED CARD

### TECHNICAL PARAMETERS TABLE

|                              |             |                                             |                                                                             |
|------------------------------|-------------|---------------------------------------------|-----------------------------------------------------------------------------|
| Index:                       | 703836      | Ingress protection:                         | IP41                                                                        |
| Nominal power [W]:           | 50          | Net weight [kg]:                            | 20                                                                          |
| Colour temperature [K]:      | 3000        | Category type:                              | louvres                                                                     |
| Luminous flux [lm]:          | 4650        | Luminaire rated power $P_{\text{min}}$ [W]: | 50                                                                          |
| Colour of the body:          | white       | ETIM class:                                 | EC002892                                                                    |
| Energy efficiency class:     | F           | Photobiological safety:                     | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Electrical protection class: | II          | CE certificate:                             | <a href="#">225/2023</a>                                                    |
| Colour rendering index:      | >80         | Warranty [years]:                           | 2                                                                           |
| SDCM:                        | ≤ 3         | Manual:                                     | <a href="#">Download PDF</a>                                                |
| Dimensions (H/W/T/S) [mm]:   | 900/900/120 | Plik LDT:                                   | <a href="#">Download</a>                                                    |

Card creation date: 02 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 225/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)