

# INDUSTRY SLIM LED 590MM 4200LM 850 IP66 105D LS2 (28W)

---

DETAILED CARD



# INDUSTRY SLIM LED 590MM 4200LM 850 IP66 105D LS2 (28W)

DETAILED CARD

## TECHNICAL PARAMETERS

|                                    |                    |
|------------------------------------|--------------------|
| Ingress protection:                | IP66               |
| Rated power of the luminaire [W]*: | 28                 |
| Luminous flux [lm]*:               | 4200               |
| Colour temperature [K]:            | 5000               |
| Material of the body:              | aluminium          |
| Colour of the body:                | grey               |
| Diffuser material:                 | PC                 |
| Diffuser type:                     | OPAL               |
| Mounting version:                  | surface, suspended |

## CHARACTERISTICS

Industry Slim Led - a brand new industrial luminaire is characterized by high luminous flux and very high luminous efficiency >160 lm/W, which makes this luminaire highly energy-efficient and environmentally friendly. It is distinguished by its very high IP66 tightness. It owes this tightness to its well-thought-out design. The polycarbonate diffuser is permanently attached to the housing with a durable silicone gasket. This means that in addition to the tightness thus achieved, the light module is protected from uncontrolled interference and access to the LEDs. The tightness of the lamp, is ensured by the gland, which screwed tightens the gasket and prevents the penetration of dust or moisture and water. Industry Slim Led allows for pendant or surface mounting.

## APPLICATION

The luminaire is designed to illuminate industrial and warehouse facilities, due to its minimal dimensions, also in hard-to-reach places. The Industry Slim Led luminaire is available in various versions: with different optics, wide, narrow, and dedicated to high-bay light distribution, and five types of the diffuser, including an anti-glare diffuser.

## DETAILS




# INDUSTRY SLIM LED 590MM 4200LM 850 IP66 105D LS2 (28W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                                   |               |                            |                              |
|-----------------------------------|---------------|----------------------------|------------------------------|
| Index:                            | 935022        | LED lifespan L80B20 [h]:   | 113000 (Ta 25°C)             |
| Rated power of the luminaire [W]: | 28            | LED lifespan L90B10 [h]:   | 54000                        |
| EAN:                              | 5905963935022 | Diffuser material:         | PC                           |
| Colour temperature [K]:           | 5000          | Material of the body:      | aluminium                    |
| Luminous flux [lm]:               | 4200          | Colour of the body:        | grey                         |
| Supply voltage [V]:               | 220 - 240     | Dimensions (H/W/T/S) [mm]: | 651/50/75                    |
| Beam angle [°]:                   | 105           | Ingress protection:        | IP66                         |
| Frequency [Hz]:                   | 50 - 60       | Impact resistance:         | IK09                         |
| Light distribution type:          | symmetric     | Mounting version:          | surface, suspended           |
| Luminous efficacy [lm/W]:         | 150           | Working temperature [°C]:  | from -25 to +35              |
| Through wiring:                   | LS2           | Wire type:                 | 5x1,5                        |
| Energy efficiency class:          | C             | Net weight [kg]:           | 1.500                        |
| Electrical protection class:      | I             | Warranty [years]:          | 5                            |
| Colour rendering index:           | >80           | CE certificate:            | <a href="#">167/2023</a>     |
| SDCM:                             | ≤ 3           | ENEC Certificate:          | <a href="#">0362/ENEC/24</a> |
| LED lifespan L70B50 [h]:          | 179000        | Manual:                    | <a href="#">Download PDF</a> |
|                                   |               | Plik LDT:                  | <a href="#">Download</a>     |

## LIGHT CURVES




# INDUSTRY SLIM LED 590MM 4200LM 850 IP66 105D LS2 (28W)

DETAILED CARD

## ACCESSORIES AVAILABLE

| index    | Name                                                              |
|----------|-------------------------------------------------------------------|
| 908200   | TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) |
| 60000006 | M16 stuffing box plug various PA black M-16 - BPM-21              |



TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) (908200)



M16 stuffing box plug various PA black M-16 - BPM-21 (60000006)

Card creation date:19 March 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric andelectronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 167/2023