


# PRODUCT DATASHEET

## LS AY VAL -CSW/P4/50

Connectors for RGB LED Strips | Connectors for RGB LED Strips



VALUE  
CLASS

---

### Areas of application

- General indoor illumination

---

### Product benefits

- Easy installation of connector, no manual wiring required
- Tool-free installation

TECHNICAL DATA

Electrical data

Nominal voltage	24 V
Nominal current	3000 mA

Dimensions & Weight

Length	98.5 mm
Cable length	50 mm
Width	14.6 mm
Height	7.7 mm
Cable cross-section, input side	0.5 mm <sup>2</sup>
Product weight	36.00 g

Colors & materials

Product color	Transparent/Black
---------------	-------------------

Temperatures & operating conditions

Ambient temperature range	-15...+50 °C
Temperature range in operation	-15...+50 °C


Certificates & Standards

Type of protection	IP00
--------------------	------

LOGISTICAL DATA

Temperature range at storage	-20...+85 °C
------------------------------	--------------

DOWNLOAD DATA

Documents and certificates		Document name
	Declarations of conformity	CE declaration LS AY VAL

Tender texts		Document name
	Tender documents	Connectors for RGB LED Strips CSWP450-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075407862	BAG 2	80 mm x 120 mm x 5 mm	37.00 g	0.05 dm <sup>3</sup>

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075407879	Shipping box 100	180 mm x 100 mm x 180 mm	3729.00 g	3.24 dm <sup>3</sup>
4058075407886	Shipping box 1,000	520 mm x 380 mm x 210 mm	38057.00 g	41.50 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.