HELEDON maxi


901762.003.3.76 | Recessed downlights





Recessed downlights 4051859870920 D 162, H 3

Recessed ceiling mounting deep black, matt (RAL 9005)



Round recessed downlight. Housing: die-cast aluminium, powder-coated. Black plastic ring and recessed LED to prevent glare from the side. Optical assembly with lens made of plastic (polycarbonate) for the best homogeneous light distribution - can be changed without tools. Best colour rendering index Ra>90. Suitable for Recessed ceiling mounting. Installation without tools thanks to spring fastening system. Including separate LED converter with connecting cable 600 mm. High quality converter without flickering and stroboscopic effect. Through-wiring box (5 pole) available as accessory. The following accessories can be mounted without use of tools: interchangeable lenses, decorative glasses, honeycomb louvre, clear and frosted diffusers, white interchangeable plastic ring.

Product specifications

Product specifications		
Diameter D	162 mm	
Height H	3 mm	
Cut-out diameter DA	152 mm	
Luminaire: recess height HEL	135 mm	
Ceiling thickness S	1-20 mm	
Installation space length LE	550 mm	
Installation space width BE	350 mm	
Installation space height HE	200 mm	
Weight	0.88 kg	
Light source	LED	
Colour temperature	3500 K	
Rated luminous flux	2850 lm	
System power	25 W	
System efficiency	114 lm/W	
Glare evaluation UGR (4H 8H)	14,8	
Beam angle	42°	
Rated life	50000 h (L90/B10)	
Colour rendering index (CRI)	92	
Colour tolerance	2	
Photobiological safety according to EN 62471	Risk group 1	
Driver	Converter, dimmable	
Control	DALI	
Voltage	220 - 240 V / 50 Hz, 60 Hz	
Luminaires on B10A fuse	21	
Luminaires on B16A fuse	34	
Luminaires on C10A fuse	35	
Luminaires on C16A fuse	57	
Inrush current / Inrush current duration	18 A / 250 μs	
CIE Flux Code / CEN Flux Code	96 100 100 100 100	
Type of protection	IP 20	
Protection class	II	
Filament test	650 °C	
Impact resistance	IK06	
Ambient temperature	-20 °C + 25 °C	
Safety marks	Do not cover the recessed luminaire!	
Conformity mark	CE, EAC	

HELEDON maxi

901762.003.3.76 | Recessed downlights



Accessories



982373.003 Spot lens



982373.023 Flood lens



982374.000 Diffuser, transparent



982422.002 White plastic ring for lens.



982372.013 Reflector medium



982372.033 Reflector wide flood



982649.002 Decorative glass opal matt



982703.002 Through-wiring box



982373.013 Medium lens



982375.003 Anti-glare honeycomb louvre



982374.010 Diffuser, satinated



982372.003 Reflector spot



982372.023 Reflector flood



982420.002 White plastic ring for reflector.



982650.002 Decorative glass opal matt