
Cesar Jazz



96701355 CESAR JAZZ 4W 360 1L 930NB RD ANT





Cesar Jazz

Cesar Jazz a wall mounted, architectural LED luminaire for decorative facade lighting, 4 window, narrow beam distribution. Fixed output Remote LED driver. Class II electrical, IP65, Impact strength: IK10. Housing: die-cast aluminium, powder coated anthracite. Working ambient temperature: -20°C to +50°C. Complete with 3000K LED.


Dimensions: Ø180 x 180 mm Luminaire input power: 18.1 W Luminaire luminous flux: 312 lm Luminaire efficacy: 17 lm/W

Weight: 3.58 kg





TLG_CESA_M_JAZZ_M_360.wmf



96701355.ldt

Lamp position: STD - standard

Light Source: LED

Luminaire luminous flux*: 312 lm Luminaire efficacy*: 17 lm/W Colour Rendering Index min.: 90

Correlated colour temperature*: 3000 Kelvin

Chromaticity tolerance (initial MacAdam): 3

Rated useful life (B10)*: L80 70000 h at 25 °C Ballast: 1x LED DRV

Luminaire input power*: 18.1 W

Dimming: FIX

LOR: 1,00 ULOR: 0,18 DLOR: 0,82

This product contains a light source of energy efficiency class F.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.