

DEEP

RECESSED SURFACE MOUNTED PANEL

STH20903PTO/40



17W

Power

1350lm

Luminous flux

120°

Beam angle




TECHNICAL SPECIFICATIONS TABLE

Beam angle	120°
Luminous efficacy	79lm/W
Power factor	0,92
Luminous flux	1350lm
Frequency	50/60Hz
CRI (Color rendering index)	80
Power	17W
Correlated color temperature (CCT)	4000K
Operation temperature	-10°C ~ 40°C
Voltage (V)	100-240V
Voltage (Vac)	100-240Vac
Lifespan	25000h

Technical Drawing

STH20903



OTHER INFORMATION

Finishing	Black
Color temperature	Neutral white
Dimmable	No
Warranty	2 years
Patent information	Patented product
Prevailing material	Polycarbonate


Graphics

STH20903PTO

1m	527lx	2,5m
2m	132lx	4,9m
3m	59lx	7,4m
4m	33lx	9,9m
5m	21lx	12,3m

h, Emax, ø

STH20903PTO



C0/180 C90/270

DOWNLOADS

[↓ IES FILE - STH20903PTO/40](#)
[↓ MANUAL DEEP](#)
[↓ SKETCHUP - STELLA - STH20903BR-30-40 - STH20903PTO-30-40 - DEEP 18W_PACK.zip](#)
[↓ REVIT - STH20903BR_30_40_STH20903PTO_30_40.rfa](#)
