TERRANO DUO 2X600X30MM 2X1650LM 830 II CL. WHITE 60D (23W)

DETAILED CARD

TECHNICAL PARAMETERS

Light source:	LED module
Rated power of the luminaire [W]*:	23
Luminous flux [lm]*:	3300
Supply voltage [V]:	220-240
Energy efficiency class:	G
Electrical protection class:	II
Colour temperature [K]:	3000
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	17/568/33

CHARACTERISTICS

The new linear luminaire in the form of a compact louver with LEDs and focusing lenses enables extremely effective glare reduction (UGR between 12 and 19). Terrano luminaires are characterised by excellent performance and many conveniences. Above all, it can be installed quickly on the supporting structure of a modular ceiling. The same luminaire can be relocated just as quickly. Changing the location will leave no trace of the mounting holes. For convenience and aesthetics, the luminaire has an extra-thin power cable, which fits between the structure and the ceiling tile. Terrano, a plastic luminaire in a slim steel housing, is available in two colour temperatures, 3000 K and 4000 K, and in two colours, white and black.

APPLICATION

Terrano can be fitted directly into modular ceiling profiles to provide general lighting, but can also be used to spotlight selected elements of a space. Terrano will become both a striking element of modern arrangements where lighting plays a key role and a complement to subtle, minimalist spaces.
*DUO- version of double lamp on one power supply

TERRANO DUO 2X600X30MM 2X1650LM 830 II CL. WHITE 60D (23W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	937316	**Diffuser type:**	matrix led
EAN:	5905963937316	**Diffuser colour:**	transparent
Light source:	LED module	**Optics:**	lens
Rated power of the luminaire [W]:	23	**Optics material:**	PMMA
Colour of the body:	white	**Material of the body:**	powder coated steel
Luminous flux [lm]:	3300	**Version:**	DUO*
Colour temperature [K]:	3000	**Dimensions (H/W/T/S) [mm]:**	17/568/33
Supply voltage [V]:	220-240	**Ingress protection:**	IP20
Frequency [Hz]:	50-60	**Mounting version:**	to T-profile ceilings suspended
Luminous efficacy [lm/W]:	143	**Working temperature [°C]:**	from -10 to +35
Energy efficiency class:	G	**LED lifespan L70B50 [h]:**	156000
Electrical protection class:	II	**LED lifespan L80B20 [h]:**	98000
Colour rendering index:	>80	**LED lifespan L90B10 [h]:**	47000
SDCM:	≤ 3	**Net weight [kg]:**	0.650
Beam angle [°]:	60	**Manual:**	Download PDF
Light distribution type:	symmetric	**CE certificate:**	68/2025
Surge protection [kV]:	2	**Category type:**	louvres
Diffuser material:	PMMA	**Plik LDT:**	Download

LIGHT CURVES



TERRANO DUO 2X600X30MM 2X1650LM 830 II CL. WHITE 60D (23W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
937408	Terrano white connector
937415	Terrano black connector



Terrano white connector (937408)



Terrano black connector (937415)

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 68/2025

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl