

PRODUCT DATASHEET

Vintage 1906 Big Elipse 6 Magnetic DIM 4W 818 Smoke E27

VINTAGE 1906 LED DECORATIVE BULB WITH FILAMENT-MAGNETIC STYLE DIMMABLE | Dimmable LED lamps, decorative bulbs with filament-magnetic technology



Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination

Product benefits

- Very low energy consumption
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Type of protection: IP20, Ideal for indoor use
- Decorative lamps with innovative LED "filament-magnetic" technology
- No Filament Holder: Perfect for decorative installations
- Available in various bulb shapes and diameters

Product features

- Lifetime up to 15,000 h
- Good quality of light; color rendering index $R_a \geq 80$; constant chromaticity
- Lamp made of plastic



- Pleasant light: Warm white comfort light color
- Can be used directly as luminaire
- Dimmable


TECHNICAL DATA

Electrical data

Nominal wattage	4 W
Construction wattage	4.00 W
Nominal voltage	220...240 V
Operating mode	AC Mains
Claimed equiv. conventional lamp power	6 W
Nominal current	21 mA
Type of current	AC
Inrush current	0.2 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	380
Max. lamp number on MCB B16 A	609
Total harmonic distortion	≤ 60 %
Power factor λ	≥ 0.40

Photometrical data

Luminous flux	60 lm
Luminous efficacy	15 lm/W
Lumen main.fact.at end of nom.life time	0.93
Light color (designation)	Comfort warm white
Color temperature	1800 K
Color rendering index Ra	80
Light color	818
Standard deviation of color matching	≤6 sdcn
Flickering metric (Pst LM)	≤1
Stroboscope effect metric (SVM)	≤0.4



Spectral graph Vintage 1800 K
MAG

Light technical data

Beam angle	320 °
Warm-up time (60 %)	0.50 s
Starting time	< 0.5 s

Dimensions & Weight

Overall length	165.00 mm
Diameter	215.00 mm
Maximum diameter	215 mm
Product weight	290.00 g

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
Maximum temperature at tc test point	48 °C

Lifespan

Lifespan L70/B50 at 25 °C	15000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.93

Additional product data

Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Clear
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Capabilities

Dimmable	Yes ¹⁾
----------	-------------------

¹⁾ Check dimmer compatibility at [ledvance.com/compatibility](https://www.ledvance.com/compatibility)

Certificates & Standards

Type of protection	IP20
Standards	CE / UKCA / EAC
Photobiological safety group acc. to EN62778	RG1

Country-specific categorizations

Order reference	1906LBELPD 4W/8
-----------------	-----------------

LOGISTICAL DATA

Temperature range at storage	-20...+80 °C
------------------------------	--------------





Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E27
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Standby power	0 W
Claim of equivalent power	Yes
Length	165.00 mm
Height	215.00 mm
Width	215.00 mm
R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	0.9
Displacement factor	≥0.5
LED light source replaces a fluorescent light source	No

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

Documents and certificates		Document name
	On-Pack-Info	ELR - exempt lamps
	Declarations of conformity	LED lamp
	Declarations of conformity UKCA	LED lamp
Photometric and lighting design files		Document name
	Spectral power distribution	Spectral graph Vintage 1800 K MAG

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075836440	Folding box 1	233 mm x 233 mm x 220 mm	565.00 g	11.94 dm ³
4058075836457	Shipping box 4	484 mm x 484 mm x 249 mm	3375.00 g	58.33 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.