

S.GROUND

LED INGROUND

STL23708/30



11,5W

Power

950lm

Luminous flux

36°

Beam angle




TECHNICAL SPECIFICATIONS TABLE

Lifespan	25000h
Voltage (Vac)	100-240Vac
Voltage (V)	100-240V
Correlated color temperature (CCT)	3000K
Power	11,5W
Luminous intensity	3100cd
CRI (Color rendering index)	80
Ingress protection rating (IP)	IP67
Frequency	50/60Hz
Luminous flux	950lm
Power factor	0,92
Luminous efficacy	82lm/W
Beam angle	36°

Technical Drawing

STL23708




Graphics

STL23708

1m	2702lx	0,6m
2m	675lx	1,3m
3m	300lx	1,9m
4m	169lx	2,6m
5m	108lx	3,2m

h, Emax, Ø

STL23708



— C0/180 — C90/270

OTHER INFORMATION

Prevailing material	Aluminum
Patent information	Patented product
Warranty	2 years
Dimmable	No
Color temperature	Warm white
Finishing	Black

DOWNLOADS

[↓ IES FILE - STL23708/30](#)
[↓ MANUAL S.Ground](#)
[↓ SKETCHUP - STELLA - STL23708-30 - EMBUTIDO DE SOLO GROUND 11W SEM GRADE_PACK.zip](#)
[↓ REVIT - STL23708_30.rfa](#)
