

# PRODUCT DATASHEET DP HOUSING 1200 E 2XLAMP IP65

# DAMP PROOF HOUSING E IP65 | Damp-proof luminaires, classic shape

#### Areas of application

- Parking lots, warehouses, production areas
- Car parks and underpasses
- Garages



## Product benefits

- Easy and quick installation
- Prewired for easy installation of tubular EM LED lamps
- Toolless installation
- Robust housing
- Sustainable solution thanks to exchangeable light sources
- 3 years guarantee

#### **Product features**

- Luminaire housing, available for 1 or 2 T8 LED tubes
- Suitable for LED TUBE T8 EM
- Type of protection: IP65

#### **TECHNICAL DATA**

# Electrical data

Protection class	11

-

#### Photometrical data

Luminous intensity

# Dimensions & Weight

Length	1265.00 mm
Width	102.00 mm
Height	65.00 mm
Product weight	730.00 g



# Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Polycarbonate (PC)
Cover material	Polycarbonate (PC)
Light emitting surface material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

# **Application & Mounting**

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+80 °C
Type of connection	Screw terminal, 2-Pole (L,N)
Type of protection	IP65
Protection class IK (shock resistance)	IK08
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling
Application environment	Indoor
With light source	No

#### **Certificates & Standards**

Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

## EQUIPMENT / ACCESSORIES

- All required accessories included

- Through-wiring cable kit available

# DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	DP HOUSING
PDF	Legal information	DP HOUSING
POF	Declarations of conformity	DP HOUSING

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854463839	Folding box 1	1,271 mm x 102 mm x 52 mm	880.00 g	6.74 dm <sup>3</sup>
4099854463846	Shipping box 12	1,288 mm x 325 mm x 228 mm	11840.00 g	95.44 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **References / Links**

- For Guarantee see www.ledvance.com/guarantee

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.