

LIGHTSTREAM midi

722286.1131.1 | Spotlights



Spotlights
4051859956686
L 516, B 220, H 56

Pole mounting, Universal mounting system
anthracite metallic (DB703)



Clever combination of spotlight and pole luminaire in one. Housing made of corrosion-resistant die-cast aluminium, seawater resistant powder-coated. Tilt angle can be adjusted and locked in 5 degree steps featuring angular scale. With membrane valve as a standard to avoid condensed water. Cover clear single-pane toughened glass, edge printed. Cover screwed to housing. Lens system made of plastic (PMMA). Replaceable LED spot modules according to ZHAGA standards. Asymmetrical linear light distribution for narrow streets and paths according to DIN EN 13201 Constant light output (CLO). With NFC programming interface. Pre-assembled connection cable, length 8 m. Modular design: Mounting set must be ordered separately.

Product specifications

Length L	516 mm
Width B	220 mm
Height H	56 mm
Weight	5.8 kg
Light source	LED
Colour temperature	4000 K
Rated luminous flux	13800 lm
System power	93 W
System efficiency	148 lm/W
Glare evaluation UGR (4H 8H)	37,7
Beam angle	69°/43°/69°/2°
Rated life	100000 h (L90/B50)
Colour rendering index (CRI)	70
Colour tolerance	5
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter
Control	on/off
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	7
Luminaires on B16A fuse	11
Inrush current / Inrush current duration	65 A / 160 µs
CIE Flux Code / CEN Flux Code	44 80 99 100 100
Type of protection	IP 66
Protection class	I
Filament test	960 °C
Impact resistance	IK08
Ambient temperature	-20 °C ... + 40 °C
Conformity mark	CE

Accessories



61199.009
Fuse box



982977.003



982058.000
Wall bracket, 500 mm, uncoated



982086.000
Wall bracket, 1000 mm, uncoated



982049.000
Pole attachment (double): for spigot 60 mm, unpainted



982050.000
Pole attachment (double): for spigot 76 mm, unpainted



982524.0031
Adapter set for 4-fold configuration (4 x 90°)



982093.000
Pole clip for pole diameter 115 - 135 mm



982591.0031
Wall bracket, powder-coated



982588.0031
Pole bracket for 2 luminaires, powder-coated



982589.0031
Pole bracket for 3 luminaires, powder-coated



982590.0031
Pole bracket for 4 luminaires, powder-coated




982983.000
Reducing adapter Ø 42 mm




982638.003
Junction box H with strain relief.



982974.003



982058.0031
Wall bracket, 500 mm, anthracite metallic



982086.0031
Wall bracket, 1000 mm, anthracite metallic



982049.0031
Pole attachment (double): for spigot 60 mm, anthracite metallic (DB703)



982050.0031
Pole attachment (double): for spigot 76 mm, anthracite metallic (DB703)



982092.000
Pole clip for pole diameter 95 - 114 mm



982591.000
Wall bracket, uncoated



982588.000
Pole bracket for 2 luminaires, uncoated



982589.000
Pole bracket for 3 luminaires, uncoated



982590.000
Pole bracket for 4 luminaires, uncoated



982562.000
Reducing adapter Ø 60 mm

Modules



982978.0031
Pole attachment for 76 mm spigot.



983117.0031
Mounting bracket



983164.0031
Mounting bracket