


INSTRUCTION




Less is more 27
312177.003.1.76



~ 220 - 240 V 50/60 Hz IP 20, IP 20 IK00



5 x 1,5 mm ² 1,50 mm ²		Umgebungstemperatur / temperature ambiante => -25 °C ... + 25 °C	
---	--	--	--



1 2 3 [mm]	[mm]		
------------	------	--	--

L 1014, B 38, H 2, HEL 37 LA 1006, BA 30, HE 45-60, S 10-30 0,94 kg

	Φ [lm]	P [W]	P [W]			
--	-------------	---------	---------	--	--	--

LED 2350 25 1 x 21,8 W

CCT [K]	CRI	RG	EEK			
---------	-----	----	-----	--	--	--


4000 82 RG 1 E

I_{max} $I_{max}/2$ t_{50}	B10 [St.]	B16 [St.]	C10 [St.]	C16 [St.]	$\cos \varphi$	
--------------------------------	-----------	-----------	-----------	-----------	----------------	--

41 A / 150 μ s 13 21 22 36 0,95

1 2 3 [mm]			
------------	--	--	--

LG 346, BG 32, HG 22





Installation erfordert
Elektro-Fachkraft!

Symbole nach ISO 7010



Allgemeine Sicherheitshinweise

- Der elektrische Anschluss muss ordnungsgemäß nach geltenden Normen und den nationalen sowie internationalen Sicherheits- und Unfallverhütungsvorschriften erfolgen.
- Beschädigte Leuchten dürfen nicht betrieben werden.
- Keine Haftung für Schäden durch unsachgemäßen Einsatz.
- Bei Instandsetzung nur Originalteile verwenden.
- Tragfähigkeit der Decke und Befestigungselemente sicherstellen.

Betrieb der Leuchte

- Die unzulässigen Umgebungstemperaturen reduzieren die Lebensdauer der Leuchte, im Extremfall droht der Frühausfall.
- Zur Vermeidung von EMV-Problemen die Durchgangsverdrahtung nicht entlang der Leuchtenverdrahtung führen.
- Steuereingänge von dimmbaren Leuchten mit handelsüblichen für Netzspannung geeigneten Leitungen anschließen.

Manipulationen unserer Produkte sind unzulässig

Veränderung, Umarbeitung, Umkennzeichnung von Produkten sowie deren Verpackung sind unzulässig und verletzen u.a. unsere eingetragenen Warenzeichenrechte. Solche Modifikationen können technische Eigenschaften unserer Produkte negativ beeinflussen, diese zerstören und möglicherweise Folgeschäden an anderen Objekten verursachen. Für durch derartige Modifikationen verursachte Schäden kann der Hersteller in keinem Fall verantwortlich gemacht werden.



Installation requires
a qualified electrician!

Symbols according
to ISO 7010



General Safety Information

- Electric connection must be appropriate according to all applicable standards and other national and international safety and accident prevention regulations.
- Damaged luminaires must not be operated.
- No liability is accepted for damages resulting from improper use.
- Use genuine parts only for repair.
- Ensure stability of the ceiling and fastening elements.

Operation of the luminaire

- Exceeding the permissible ambient temperature will reduce the luminaire's lifecycle, resulting in premature failure in extreme cases.
- Avoid ESD problems by not routing feed-through wiring directly along the wiring of the luminaire.
- Connect control inputs of dimmable luminaires with standard cables suitable for power supply voltage.

Manipulation of our products is not permitted

Modifications, reworking, re-labelling of products as well as their package is not permitted and infringes, amongst others, our registered trademark rights. Such modifications may affect technical properties of our products, damage them and possibly cause consequential damage to other objects. The manufacturer shall not be responsible under any circumstances for damage caused by such modifications.



Bei Fragen zu unseren Symbolen, besuchen Sie folgende Webseite:

If you have any questions about our signs, visit the following website:




https://www.rzb.de/fileadmin/assets/downloads/PDF/RZB_Symbolklaerung.pdf



Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse E
entsprechend Verordnung (EU) 2019/2015

This product contains a light source of energy efficiency class E according to regulation (EU) No 2019/2015




Jede zersprungene Schutzabdeckung ist zu ersetzen. DIN EN 60598

Replace any cracked protective shield. IEC DIN EN 60598




Die Lichtquelle dieser Leuchte ist nicht ersetzbar, wenn die Lichtquelle ihr Lebensdauerende erreicht hat, ist die gesamte Leuchte zu ersetzen. DIN EN 60598-1 / IEC 60598-1

The light source of this luminaire is not replaceable, when light source reaches its end of life the whole luminaire shall be replaced. DIN EN 60598-1 / IEC 60598-1



Nicht zur Abdeckung mit Wärmedämm-Material geeignete Leuchten!

Not to be covered with thermal insulation material!



This diagram shows the exploded view of the LED lighting fixture assembly. The components include: a long, thin LED light bar; a power supply unit with a fan and a power cord; a mounting bracket with two screws; a small rectangular control unit; a power switch with a cord; and a rectangular control panel with four buttons. A small box is also shown in the upper right corner.

A diagram of a beam with three supports. The beam is inclined upwards from left to right. It is supported by a pin support at the left end, a roller support in the middle, and a roller support at the right end. A curved load is applied downwards on the right half of the beam.

A diagram of a mechanical press, likely a guillotine, with a large exclamation mark to its left. Two arrows point down from the press's blades towards a material being cut, with the word "click" in a starburst shape next to each arrow.

min. 45 mm

11 max.
1,5 mm²

DA - DALI ☐ DA
- braun / brown
- blau / blue
- max. 16 A!

1. Input PRI

2.





3.










4.

N D A D A

Input 6. PRI



6 max.
1.5 mm








10



11







1




2




3



4



5




6




a



b



c




d







e





f



g







RZB - Rudolf Zimmermann, Bamberg GmbH

 Rheinstraße 16, 96052 Bamberg

 0951/7909-0

 0951/7909-198

 info@rzb-leuchten.de