
## MEGA TUBE 621102.004 | Wall luminaires





Wall luminaires 4051859512196 L 160, B 115, H 338

Wall (surface) silver, matt (approx. RAL 9006)



Attractive wall luminaire with innovative housing design and high-quality LED optics. Housing made of corrosion-resistant die-cast aluminium, seawater resistant powder-coated. With membrane valve as a standard to avoid condensed water. Fixing on the wall outside the sealed volume, drill hole deviations can be compensated. Screwless luminaire fixing via RZB Gravolock® System.

**Product specifications** 

Product specifications		
Length L	160 mm	
Width B	115 mm	
Height H	338 mm	
Weight	3.02 kg	
Light source	LED	
Colour temperature	3000 K	
Rated luminous flux	650 lm	
System power	10 W	
System efficiency	65 lm/W	
Glare evaluation UGR (4H 8H)	18,7	
	down 180°	
Beam angle	up 180°	
Rated life	60000 h (L80/B50)	
Colour rendering index (CRI)	80	
Colour tolerance	3	
Photobiological safety according to EN 62471	Risk group 1	
Driver	Converter	
Control	on/off	
Voltage	220 - 240 V / 0 Hz, 50 - 60 Hz	
Luminaires on B10A fuse	39	
Luminaires on B16A fuse	63	
Luminaires on C10A fuse	63	
Luminaires on C16A fuse	100	
Inrush current / Inrush current duration	8 A / 5 μs	
CIE Flux Code / CEN Flux Code	13 38 67 44 100	_
Type of protection	IP 65	
Protection class	1	_
Filament test	960°C - 30 seconds	
Impact resistance	IK04	
Ambient temperature	-20 °C + 45 °C	
Conformity mark	CE, EAC	

## MEGA TUBE 621102.004 | Wall luminaires



## **Spareparts**



982108.014 Replacement glass