

S.GROUND

LED INGROUND

STL23727/30



6,5W

Power

520lm

Luminous flux

36°

Beam angle




TECHNICAL SPECIFICATIONS TABLE

Lifespan	25000h
Voltage (Vac)	100-240Vac
Voltage (V)	100-240V
Correlated color temperature (CCT)	3000K
Power	6,5W
Luminous intensity	1300cd
CRI (Color rendering index)	80
Ingress protection rating (IP)	IP67
Frequency	50/60Hz
Luminous flux	520lm
Power factor	0,92
Luminous efficacy	80lm/W
Beam angle	36°

Technical Drawing

STL23727



OTHER INFORMATION

Prevailing material	Aluminum
Patent information	Patented product
Warranty	2 years
Dimmable	No
Color temperature	Warm white
Finishing	Stainless steel SAE 316


Graphics

STL23727

1m	1330lx	0,6m
2m	333lx	1,3m
3m	148lx	1,9m
4m	83lx	2,6m
5m	53lx	3,2m

h, Emax, Ø

STL23727



DOWNLOADS

[↓ IES FILE - STL23727/30](#)
[↓ MANUAL S.Ground](#)
[↓ SKETCHUP - STELLA - STL23727-30 - EMBUTIDO DE SOLO GROUND 6W SEM GRADE_PACK.zip](#)
[↓ REVIT - STL23727_30.rfa](#)
