



# MASTER VALUE LEDspot MV



## MAS LED spot VLE D 4.9-50W GU10 940 60D

Delivering a warm, halogen-like accent beam, MASTER VALUE is a perfect fit for spot lighting. Thanks to its high CRI, it realizes more natural colors, creating cozy and comfortable ambiances for residential and hospitality projects, and emphasizing the beauty of merchandise in retail. These LED spots MV GU10 have the familiar look and feel of spot lamps, keeping the classic beauty of glass spots and adding the strong performance of LED technology. The dimming function enables you to create the atmosphere you desire, and it works with broad selection of dimmers. MASTER VALUE also offers more energy savings than normal LED spots.

### Warnings and Safety

- Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Not intended for use with emergency light fixtures or exit lights

### Product data

General Information	
Cap-Base	GU10
Nominal lifetime	25,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Narrow Cone
Light Technical	
Color Code	940 [CCT of 4000K]
Beam Angle (Nom)	60 degree(s)
Luminous Flux	380 lm

Luminous Intensity (Nom)	400 cd
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	85.71 lm/W
Color Consistency	<6
Color rendering index (CRI)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %
Luminous Flux in 90° Cone (Rated)	380 lm
Photobiological safety according to EN 62471	RG1

# MASTER VALUE LEDspot MV

Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	4.9 W
Lamp Current (Nom)	27 mA
Wattage Equivalent	50 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.8
Voltage (Nom)	220-240 V

Temperature	
T-Case Maximum (Nom)	80 °C

Controls and Dimming	
Dimmable	Only with specific dimmers

Mechanical and Housing	
Bulb Shape	PAR16
Net Weight (Piece)	0.038 kg


Approval and Application	
Energy Efficiency Class	F
Suitable For Accent Lighting	Yes
Energy Consumption kWh/1000 h	5 kWh

EPREL Registration Number	391892
CE mark	Yes
EU RoHS compliant	Yes
EyeComfort	Yes
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	0.4

Application Conditions	
can it be used in closed luminaires	No

Product Data	
Order product name	MAS LED spot VLE D 4.9-50W GU10 940 60D
Full product name	MAS LED spot VLE D 4.9-50W GU10 940 60D
Full product code	871869670795100
Order code	929001349302
Material Nr. (12NC)	929001349302
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696707951
Numerator - Packs per outer box	10
EAN/UPC - Case	8718696707968


## Dimensional drawing




Product	D	C
MAS LED spot VLE D 4.9-50W GU10 940 60D	50 mm	54 mm

# MASTER VALUE LEDspot MV

## Photometric data




General Parameters 4.1 Photo Lighting 8.1 Page 17





Accent Lighting Spots - MAS LED spot VLE D 4.9-50W GU10 940 60D

Spectral Power Distribution Colour - MAS LED spot VLE D 4.9-50W GU10 940 60D



Light Distribution Diagram - MAS LED spot VLE D 4.9-50W GU10 940 60D

## Lifetime



25K LED

Lumen Maintenance Diagram - MAS LED spot VLE D 4.9-50W GU10 940 60D

## MASTER VALUE LEDspot MV

