



Corepro LED Strip



CorePro LEDstrip 12.3W827 1450LM/M 5M

A complete family that are bright, slim, safe & reliable. Choose the best fit for every projects, from 4 lumen packs/wattages, and 4 CCTs, and enjoy easy installation with slimness

Product data

General Information		
Driver included	No	
Lighting Technology	LED	
Warranty period	3 years	
Light Technical		
Luminous Flux	1,450 lm	
Correlated Color Temperature (Nom)	2700 K	
Luminous Efficacy (rated) (Nom)	117.00 lm/W	
Color rendering index (CRI)	80	
Photobiological safety according to EN 62471 RG1		
Operating and Electrical		
Input Voltage	24 V	
Initial CLO power consumption	52 W	
Average CLO power consumption	0 W	
Power Consumption	52 W	
Power Factor (Fraction)	1	
Cable	Cable 0.3 m without plug	
Number of products on MCB of 16 A type B	-	
Protection class IEC	Safety class III	
Controls and Dimming		
Dimmable	Yes	

Control interface	depends on driver (1-10V, DALI)
Constant light output	No
Maximum dim level	10% (depends on dimmer, ELV)
Mechanical and Housing	
Reflector material	-
Overall length	5,000 mm
Overall width	8 mm
Overall height	1.3 mm
Dimensions (Height x Width x Depth)	1 x 8 x 5000 mm
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK00 [No protection]
Net Weight (Piece)	0.100 kg
Approval and Application	
Energy Efficiency Class	F
EPREL Registration Number	620709
Glow-wire test	Temperature 650 °C, duration 30 s
CE mark	Yes
EU RoHS compliant	Yes
Ambient temperature range	-20 to +40 °C
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%

Datasheet, 2025, March 11 data subject to change

Corepro LED Strip


Initial chromaticity	(0.4578, 0.4101) 5SDCM
Power consumption tolerance	+/-10%
Over Time Performance (IEC Con	npliant)
Median useful life L70B50	35,000 hour(s)
Product Data	
Order product name	CorePro LEDstrip 12.3W827 1450LM/M
	5M
Full product name	CorePro LEDstrip 12.3W827 1450LM/M
	5M

Full product code	871951434424200
Order code	929002695902
Material Nr. (12NC)	929002695902
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514344242
Numerator - Packs per outer box	10
EAN/UPC - Case	8719514344259

Dimensional drawing




Photometric data



Circulat Progressio 42.1 Philes Lighting 6.V. Page 17

General uniform lighting - CorePro LEDstrip 12.3W827 1450LM/M 5M



Light Distribution Diagram - CorePro LEDstrip 12.3W827 1450LM/M 5M

Corepro LED Strip



© 2025 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.