

ALTEZZO L 150 K 5200LM 840 IP65 RAL7016 40W

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP65
Impact resistance:	IK08
Luminous flux [lm]*:	5200
Colour temperature [K]:	4000
Material of the body:	aluminium
Colour of the body:	RAL7016
Diffuser material:	PC
Beam angle [°]:	110
Mounting version:	surface
Dimensions (H/W/T/S) [mm]:	150/150/500

CHARACTERISTICS

The Altezzo L 150 K wall lamp completes the entire line of outdoor lighting from the Altezzo series. It is characterized by a classic, simple shape and good light and mechanical parameters. It is available with three light color temperatures 2700 K 3000 K and 4000 K.

APPLICATION

The sconce's high IP65 waterproofing and IK08 impact resistance allow it to be used outdoors. It will prove useful as lighting for facades and building surroundings. Together with other products of the Altezzo line, it will provide good, eye-friendly and safety-friendly lighting and design consistency in housing estates, parks and gardens.

ALTEZZO L 150 K 5200LM 840 IP65 RAL7016 40W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	984365	Colour of the body:	RAL7016
EAN:	5905963984365	Mounting dimensions [mm]:	75x75 - 90x90
Light source:	LED module	Impact resistance:	IK08
Rated power of the luminaire [W]:	40	Ingress protection:	IP65
Luminous flux [lm]:	5200	Mounting version:	surface
Luminous efficacy [lm/W]:	130	Working temperature [°C]:	od - 30 do + 50
Colour temperature [K]:	4000	Net weight [kg]:	3.200
Energy efficiency class:	D	CE certificate:	181/2023
Beam angle [°]:	110	Warranty [years]:	5
Electrical protection class:	I	Category type:	accent lighting
Dimensions (H/W/T/S) [mm]:	150/150/500	Light distribution type:	general
Colour rendering index:	>70	Manual:	Download PDF
Diffuser material:	PC	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Material of the body:	aluminium		

Card creation date: 09 January 2025
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 181/2023