

EXPO ADJUST 1950LM ZOOM 22-55° BLACK 940 19W

DETAILED CARD



TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	19
Luminous flux [lm]*:	1950
Colour temperature [K]:	4000
Diffuser material:	PC
Diffuser type:	clear
Diffuser colour:	transparent
Material of the body:	aluminium
Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	225/213/95
Warranty [years]:	5

CHARACTERISTICS

EXPO ADJUST are top quality aluminum projectors with LED COB light source. Mounted on a rail system, it increases the range of applications and allows the user to make rearrangement changes even after installation. The compact, small-sized aluminum body with a heat sink effectively dissipates excess heat from the projector and increases the life of the product. Expo Adjust projectors are friendly to people and the environment. They are innovative, highly energy-efficient projectors with excellent light efficiency and a minimalist, distinctive design.

APPLICATION

No emission of ultraviolet and infrared radiation and a high color rendering index (Ra <90), combined with the highest luminous efficiency and excellent product durability, allows the use of EXPO ADJUST wherever the highest quality of light is expected while maintaining energy efficiency. The main areas of application are accent lighting in commercial facilities, museums, exhibition halls, offices, and apartments.

The ZOOM version with adjustable lighting angle in the range of 22-55° increases the adaptive value of the product in the event of a change in the decor or the need for a different display of goods compared to the original assumptions.

EXPO ADJUST 1950LM ZOOM 22-55° BLACK 940 19W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	481383	Diffuser type:	clear
Rated power of the luminaire [W]:	19	Diffuser colour:	transparent
EAN:	5905963481383	Optics material:	PC
Luminous flux [lm]:	1950	Optics:	lens
Light source:	COB	Tilt angle adjustment [°]:	yes; 22-55°
Colour temperature [K]:	4000	Dimensions (H/W/T/S) [mm]:	225/213/95
Nominal power [W]:	17.50	Ingress protection:	IP20
Colour rendering index:	>90	Working temperature [°C]:	from -20 to +25
Supply voltage [V]:	220 – 240	Energy efficiency class:	E
Mounting version:	track	Net weight [kg]:	0.730
Frequency [Hz]:	50 - 60	Light distribution type:	symmetric
Material of the body:	aluminium	Warranty [years]:	5
Luminous efficacy [lm/W]:	103	CE certificate:	214/2023
Electrical protection class:	I	Manual:	Download PDF
Colour of the body:	black	ETIM class:	EC001744
SDCM:	≤ 3	Plik LDT:	Download
Beam angle [°]:	22-55		
Diffuser material:	PC		

Card creation date: 02 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 214/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl