

LUNGO 825 LM 50 ST FI60 H145 I KL IP20 NT WHITE 830 (10W)

DETAILED CARD



TECHNICAL PARAMETERS

Light source:	COB LED
Ingress protection:	IP20
Nominal power [W]:	10
Luminous flux [lm]*:	825
Colour temperature [K]:	3000
Colour rendering index:	>80
Energy efficiency class:	F
Material of the body:	aluminium
Colour of the body:	white
Diffuser material:	PMMA

CHARACTERISTICS

The family of lungo luminaires will make each interior stylish and original. The option to combine different sizes and colours of luminaires allows creating original compositions which will be a decorative embellishment of rooms arranged in a modern way.

APPLICATION

The luminaire is intended for indoor traffic zones included in table 5.1 of the EN12464 standard.

LUNGO 825 LM 50 ST FI60 H145 I KL IP20 NT WHITE 830 (10W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	10	Diffuser material:	PMMA
Light source:	COB LED	Diffuser type:	PRM
Colour temperature [K]:	3000	Optics material:	PMMA
Luminous flux [lm]:	825	Optics:	lens
Supply voltage [V]:	220-240	Material of the body:	aluminium
Beam angle [°]:	50	Mounting dimensions [mm]:	36
Frequency [Hz]:	50 - 60	Ingress protection:	IP20
Colour of the body:	white	Mounting version:	surface
Luminous efficacy [lm/W]:	82	Working temperature [°C]:	from -20 to +35
Dimensions (H/W/T/S) [mm]:	60/145	Net weight [kg]:	0.250
Energy efficiency class:	F	CE certificate:	229/2023
Electrical protection class:	I	Index:	645211
Colour rendering index:	>80	EAN:	5905963637384
SDCM:	≤ 3	Category type:	downlights
Power factor:	0.99	Warranty [years]:	2
LED lifespan L70B50 [h]:	40000	Manual:	Download PDF
		Plik LDT:	Download

LIGHT CURVES

