

PRODUCT DATASHEET TRUSYS FLEX P RAIL 1500 8P END WT

TruSys® FLEX ENERGY RAIL 8-POLE | 8-pole mounting rail



- Industry halls, high rack warehouse, hardware stores





Product benefits

- Simple installation
- High flexibility thanks to three available lengths (1500 mm, 3000 mm, 4500 mm and 1500 mm end rail)
- Version of 600 mm rail to be used with TRUSYS FLEX SENSOR TRACK

Product features

- Through wired with 8 core cable
- Different lenghts available
- Electrical connection internal at the first luminaire, no external connection unit required
- Steel-sheet housing
- End-Rail without electrical and mechanical connectors



TECHNICAL DATA

Dimensions & Weight

Length	1500 mm
Width	70.2 mm
Height	38.8 mm
Product weight	1400.00 g



TRUSYS FLEX RAIL END

Materials & Colors

Product color	White
Body material	Steel

Application & Mounting

Mounting location	Ceiling
With light source	No

Certificates & Standards

Standards	CE / CB / UKCA / ENEC / EAC

EQUIPMENT / ACCESSORIES

- Various accessories available

DOWNLOAD DATA

	Documents and certificates	Document name
POF	User instruction / safety instru	ctions TRUSYS FLEX P RAIL
POF	Legal information	Informationstext 18 Abs 4 ElektroG
POF	Declarations of conformity	CE Declaration of Conformity TRUSYS FLEX
POF	Declarations of conformity Uk	CA UKCA Declaration of Conformity TRUSYS FLEX
	CAD/BIM files	Document name
	BIM Revit 3D	TRUSYS FLEX
	CAD STEP 3D	TruSys FLEX ER END 1500
	Tender texts	Document name
	Tender documents	TruSys FLEX ENERGY RAIL 8-POLE 1500 8P END WT-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075781719	Sleeve 1	43 mm x 52 mm x 1,680 mm	1412.00 g	3.76 dm ³
4058075781726	Shipping box 4	1,570 mm x 191 mm x 141 mm	6644.00 g	42.13 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.