




Lay-in luminaires  
4051859330882  
L 1197, B 297

Recessed ceiling mounting  
white



High-efficiency lay-in luminaire for ceiling systems with visible mounting rails. Housing: metal, powder-coated. Alea optical system: Reflector structure (ABS, Aluminium-coated, highly polished) with integrated diffuser made of non-yellowing plastic (PMMA) opal for glare-free light at the workstation. Narrow beam, brilliant luminous effect. Suitable for Recessed ceiling mounting. Driver integrated. Perfect for office areas (UGR ≤ 19) and environments with computer screens in accordance with EN 12464-1.

Product specifications

Length L	1197 mm
Width B	297 mm
Cut-out length LA	1175 mm
Cut-out width BA	275 mm
Installation space length LE	1200 mm
Installation space width BE	300 mm
Installation space height HE	27 mm
Weight	3.07 kg
Light source	LED
Colour temperature	4000 K
Rated luminous flux	3450 lm
System power	26 W
System efficiency	133 lm/W
Glare evaluation UGR (4H 8H)	18,5
Beam angle	78°/75°
Rated life	50000 h (L80/B10)
Colour rendering index (CRI)	80
Colour tolerance	4
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter
Control	on/off
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	14
Luminaires on B16A fuse	22
Luminaires on C10A fuse	23
Luminaires on C16A fuse	37
Inrush current / Inrush current duration	40.8 A / 100 µs
CIE Flux Code / CEN Flux Code	82 100 100 100 100
Type of protection	IP 20
Protection class	I
Filament test	650°C - 30 seconds
Impact resistance	IK03
Ambient temperature	-20 °C ... + 40 °C
Safety marks	Do not cover the recessed luminaire!
Conformity mark	CE, EAC


### Accessories



982190.012  
Surface mounting frame



982293.012  
Pendant frame



982106.002  
Mounting frame for installation in suspended ceilings.