

DEEP

RECESSED SURFACE MOUNTED PANEL

STH20902BR/40



12W

Power

1150lm

Luminous flux

120°

Beam angle




TECHNICAL SPECIFICATIONS TABLE

Beam angle	120°
Luminous efficacy	96lm/W
Power factor	0,5
Luminous flux	1150lm
Frequency	50/60Hz
CRI (Color rendering index)	80
Power	12W
Correlated color temperature (CCT)	4000K
Voltage (V)	100-240V
Voltage (Vac)	100-240Vac
Lifespan	25000h
Register Number	
Certifier Number	
Certifier	

Technical Drawing

STH20902




Graphics

STH20902BR

1m	361lx	2,5m
2m	90lx	4,9m
3m	40lx	7,4m
4m	23lx	9,9m
5m	14lx	12,3m

h, Emax, Ø

STH20902BR



OTHER INFORMATION

Finishing	White
Color temperature	Neutral white
Dimmable	No
Warranty	2 years
Patent information	Patented product
Prevailing material	Polycarbonate

DOWNLOADS

[↓ IES FILE - STH20902BR/40](#)[↓ MANUAL DEEP](#)[↓ SKETCHUP - STELLA - STH20902BR-30-40 - STH20902PTO-30-40 - DEEP 12W_PACK.zip](#)[↓ REVIT - STH20902BR_30_40_STH20902PTO_30_40.rfa](#)