

WALL MINI

WALL-MOUNTED EFFECT LIGHT | 2 NARROW BEAMS

STH9732BR/30



5W

Power

20lm
(10lm/10lm)lm

Luminous flux


4° / 4°

Beam angle

TECHNICAL SPECIFICATIONS TABLE

Beam angle	4° / 4°
Power factor	0,92
Luminous flux	20lm (10lm/10lm)
Frequency	50/60Hz
Ingress protection rating (IP)	IP65
CRI (Color rendering index)	80
Power	5W
Correlated color temperature (CCT)	3000K
Operation temperature	-10°C ~ 40°C
Voltage (V)	100-240V
Voltage (Vac)	100-240Vac
Lifespan	25000h

Technical Drawing




Graphics

STH9732BR

1m	160lx	0,1m
2m	40lx	0,3m
3m	18lx	0,4m
4m	10lx	0,6m
5m	6lx	0,7m

h, Emax, ø



OTHER INFORMATION

Finishing	White
Color temperature	Warm white
Dimmable	No
Warranty	2 years
Patent information	Patented product
Prevailing material	Polycarbonate

DOWNLOADS

MANUAL Wall Mini

SKETCHUP - STELLA - STH9732BR-30 - STH9732PTO-30 - WALL MINI - FACHO FECHADO_PACK.zip

REVIT - STH9732BR_30_STH9732PTO_30.rfa

