


# SQ 1200 4900LM PRM DALI I CL. IP20 1192X292MM 830 (44W)

DETAILED CARD



## TECHNICAL PARAMETERS

|                          |        |
|--------------------------|--------|
| Index:                   | 412455 |
| Ingress protection:      | IP20   |
| Nominal power [W]:       | 44     |
| Luminous flux [lm]*:     | 4900   |
| Colour temperature [K]:  | 3000   |
| Colour rendering index:  | >80    |
| SDCM:                    | ≤ 5    |
| Energy efficiency class: | E      |
| Material of the body:    | ABS    |
| Diffuser material:       | PS     |

## CHARACTERISTICS

The SQ 1200 LED is a new line of rectangular raster lights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic for low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Ensures low power consumption and all the advantages of modern LED lamps.

Degree of protection - dependent on mounting method:

- surface-mounted - IP20,
- flush-mounted - IP44/20.

## APPLICATION

Surface-mounted luminaire with the possibility of flush-mounting in modular ceilings and in plasterboard ceilings (using a KG frame/adaptor) is particularly recommended for office areas, spacious corridors and public spaces.

