

PRODUCT DATASHEET DP HOUSING 600 E 1XLAMP IP65

DAMP PROOF HOUSING E IP65 | Damp-proof luminaires, classic shape



Areas of application

- Parking lots, warehouses, production areas
- Car parks and underpasses
- Garages

Product benefits

- Easy and quick installation
- Prewired for easy installation of tubular EM LED lamps
- Toolless installation
- Robust housing
- Sustainable solution thanks to exchangeable light sources
- 3 years guarantee

Product features

- Luminaire housing, available for 1 or 2 T8 LED tubes
- Suitable for LED TUBE T8 EM
- Type of protection: IP65

TECHNICAL DATA

Electrical data

Protection class	
------------------	--

Photometrical data

Luminous intensity	-
Earth Todo intoriorly	

Dimensions & Weight

Length	655.00 mm
Width	65.00 mm
Height	65.00 mm
Product weight	335.00 g



DP HOUSING 600 E 1XLAMP IP65

Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Polycarbonate (PC)
Cover material	Polycarbonate (PC)
Light emitting surface material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+80 °C
Type of connection	Screw terminal, 2-Pole (L,N)
Type of protection	IP65
Protection class IK (shock resistance)	IK08
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling
Application environment	Indoor
With light source	No

Certificates & Standards

Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

EQUIPMENT / ACCESSORIES

- All required accessories included
- Through-wiring cable kit available

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	DP HOUSING
PDF	Legal information	DP HOUSING
PDF	Declarations of conformity	DP HOUSING

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854463679	Folding box	660 mm x 66 mm x 52 mm	410.00 g	2.27 dm ³
4099854463686	Shipping box 20	677 mm x 285 mm x 280 mm	9003.00 g	54.02 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.