

DIONE LED PLUS 2350 LM 830 IP65 AW 3H AT OPAL WHITE 22W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	950421
Ingress protection:	IP65
Impact resistance:	IK10
Nominal power [W]:	22
Luminous flux [lm]*:	2350
Colour temperature [K]:	3000
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	ABS
Ring material:	ABS

CHARACTERISTICS

Designed from scratch surface mounted, round LED luminaire with integrated, energy-saving LED panel. The fitting introduces new solutions to improve the light distribution and balance of the temperatures. It is characterized by high lighting efficiency and very high IP65 ingress protection. Specially profiled diffuser made of vandal-resistant PC allows keeping the highest degree of impact resistance IK10. It uses a number of proven solutions affecting the speed and ease of the assembly (suspension kit for the diffuser, readiness for through wiring) and component security: diffuser integrated with LED panel. Also available is a body made of ASA material, with excellent UV resistance, suitable for outdoor use. The ceiling ring is used to cover the gap between the luminaire and the surface on which it is mounted. The accessory can be used in prison cells.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency, and optimal use of electricity (Power Factor).

The fitting is offered in RCR version:

- sensor used to detect motion; for detection uses microwaves (active sensor).

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes) or outdoor. It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

DIONE LED PLUS 2350 LM 830 IP65 AW 3H AT OPAL WHITE

22W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	22	Ingress protection:	IP65
Light source:	LED module	Mounting version:	surface
Colour temperature [K]:	3000	Working temperature [°C]:	from 0 to +25
Luminous flux [lm]:	2350	Emergency lighting [h]:	3
Rated power of the luminaire [W]:	24	Dimensions of single box [mm]:	340/340/115
Supply voltage [V]:	220-240	Net weight [kg]:	1.300
Frequency [Hz]:	50 - 60	Gross weight [kg]:	1.480
Luminous efficacy [lm/W]:	97	Warranty [years]:	2 / 0.5 (bateria)
Energy efficiency class:	E	Permeability factor of the diffuser:	0.73
Electrical protection class:	I	Index:	950421
Colour rendering index:	>80	EAN:	5905963950421
SDCM:	≤ 3	Category type:	bulkheads
Power factor:	0.94	Autotest:	yes
Charging time [h:min]:	48	AC voltage range [V]:	220 - 240
Battery life [h:min]:	3	LED lifespan L70B50 [h]:	110000
Beam angle [°]:	120	LED lifespan L80B20 [h]:	84000
Diffuser material:	PC	LED lifespan L90B10 [h]:	33000
Diffuser type:	OPAL	Light distribution type:	open space
Diffuser colour:	white	CE certificate:	377/2023
Material of the body:	ABS	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Colour of the body:	white	Manual:	Download PDF
Ring material:	ABS	PZH certificate:	B-BK-60212-0619/20
Ring colour:	white	ENEC Certificate:	
Dimensions (H/W/T/S) [mm]:	ø340/115		
Mounting dimensions [mm]:	140		
Impact resistance:	IK10		

DIONE LED PLUS 2350 LM 830 IP65 AW 3H AT OPAL WHITE 22W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
120DL118	Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant



Ceiling ring Dione LED steel 1.5 white
matt RAL 9003 painted vandal
resistant (120DL118)

Card creation date:10 January 2025
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric andelectronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 377/2023