

# Motion detector, 230 V, 14 m, round, for flush-mounting box, white

351-25340

4 year warranty

Motion detector with strong detection, for universal use thanks to versatile accessories, external switch (ON). Ideal for passageways.

Finishing colour: white


- The motion detector for each standard applications
- Separate setting for the lux, the switch-off delay and the sensitivity
- Low consumption (0.25 W)
- Surface-mounting boxes available separately

Motion detector for the stairwell, cellar, small meeting rooms, etc.

- The lighting remains on while there is motion
- You can programme it manually or using the optional remote control
- You can always be certain of excellent detection thanks to the three PIR sensors.



## Detection range



H	A Across	B Towards
2 m	∅ 10 m	∅ 5 m
2.5 m	∅ 12 m	∅ 6 m
3 m	∅ 14 m	∅ 7 m
3.5 m	∅ 16 m	∅ 8 m
4 m	∅ 16 m	∅ 8 m
5 m	∅ 16 m	∅ 8 m
6 m	∅ 16 m	∅ 8 m



230 V



stand-alone



360°



∅ 14 m from  
a height of  
3 m



2 – 6 m



flush-  
mounting  
box

**niko**


## Technical data

Article number	351-25340
Input voltage	230 Vac $\pm$ 10 %, 50 Hz
Detector output	230 V (ON/OFF)
Maximum MCB rating	10 A (limited by national installation rules)
Relay contact	N.O. (max. 10 A)
Maximum load incandescent and halogen lamps ( $\cos\phi=1$ )	2300 W
Maximum load economy lamps (CFLi)	350 W
Maximum load LED lamps 230 V	350 W
Light intensity range	5 lux – 2000 lux
Number of channels	1 channel
Switch-off delay	pulse, 10 s – 20 min
Detection angle	360 °
Detection range (PIR)	$\varnothing$ 14 m from a height of 3 m
Ambient temperature	-20 – +40 °C
Mounting method	flush-mounting box
Mounting height	2 – 6 m
Dimensions visible (HxWxD)	105 x 105 x 35 mm
Dimensions (HxWxD)	105 x 105 x 71 mm
Protection degree	IP20
Marking	CE

## Accessories

351-25330	Deco ring, white
351-25420	Surface-mounting box, white
350-41936	Universal remote control for smartphone
351-25320	IR remote control
351-25310	IR remote control for users

## Dimensions



## Wiring diagram

