







Screw

terminal block 4mm², 1-level, earth connection, for TH15 rail

Series	TR
Code	TR200
Type	TR.4
HS code	85369010
Colour	Yellow-green
TECHNICAL FEATURES	
Function/Type	Earth terminal blocks
Rated cross-section	4 mm ²
Connecting capacity	
Flexible wire	0.2-6 mm ²
Rigid wire	0.2-6 mm ²
Wire with ferrule - ferrule type	4 mm ² - WP40/16
Electrical characteristics according to IEC EN standard	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	-
Caliber	A4
Electrical characteristics according to UL Standard	
Maximum voltage AC/DC	600 V
Maximum current (rated cross-section)	-
Section (min-max)	20-10 (AWG)
Tightening torque value (UL)	5.5 lb.in
Electrical characteristics according to ATEX directive and IEC Ex standard	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	32 A
Operating temperature Min/Max	-40 °C / +110 °C
Rated impulse withstand voltage / pollution degree	6 kV / 3
Insulation stripping length	9 mm
Tightening torque value (nom. / max.)	0.5 / 1.2 Nm
Width (pitch)	7.3 mm
Length	35 mm
Height mounted on TH35-7.5/TH35-15/G32	- / - / -
Height mounted on TH15-5.5	35 mm
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
ACCESSORIES	
End section	
Grey	-
Blue	-
Thickness	-
Cross-connection	
Coloured partition plate	DFP/2/R (cod. DFP2R)
Protection cover	-
Test plug socket	-
Screw and plate for short-circuit	
Marking	
Single marking tag for pitch insertion	-
End bracket	
TH35 screw type	BT/2 (cod. BT006)
Mounting rail	
IEC 60715/TH15	PR.2/...
APPROVALS AND MARKINGS	
	   



1 For more details on accessories, refer to the relevant chapters

DESCRIZIONE DEL PRODOTTO

TR.4 Screw terminal block 4mm², 1-level, earth connection,
for TH15 rail