

EKV3+1 70 R V4RJ7A2 (V4RJ7A2)

Bestelldaten	Typ	Beschreibung
Variantennummer V4RJ7A2	EKV3+1 70 R	3-polige Erdungs- und KurzschlieÙvorrichtung nach DIN VDE 0683 Teil 100 (EN/IEC 61230) Selbsterschritt: 70 mm ² / 35 mm ² Maximaler Kurzschlussstrom / -dauer: 19,5 kA / 0,5 s - 2,5
		Länge A: 600 mm Länge B: 600 mm Länge C: 600 mm Länge D: 1800 mm
	UK 25 SQ	Universalklemme Ø20/25 mm, Spindel mit Querstift Art.-Nr. 773 234 Datenblatt Art.-Nr. 773 234 (Typ UK 25 SQ)
	UEK 25 HG	Universalerdungsklemme Ø20/25 mm, mit Handgriff Art.-Nr. 774 234 Datenblatt Art.-Nr. 774 234 (Typ UEK 25 HG)




Figure without obligation

Type	EKV3+1 70 R V4RJ7A2
Part No.	V4RJ7A2
Phase cable end	UK 25 SQ
Earth cable end	UEK 25 HG
For fixed ball point Ø	20 / 25 mm
For T pins with a collar width of	15 mm
Rd / Fl clamping range	20 mm
Cable cross-section Cu	70/35 mm ²
Max. short-circuit current I _k 0.5 s	19.5 kA
Max. short-circuit current I _k 1 s	13.8 kA
Standard	EN/IEC 61138 (DIN VDE 0283-3) and EN/IEC 61230 (DIN VDE 0683-100)
Temperature range	-25 °C ... +55 °C
Material (cable)	E-Cu, extra finely stranded and highly flexible
Material (sheath)	Thermoplastic (soft PVC compound YM2)
Weight	5,76 kg
Customs tariff number	85359000
GTIN	4013364165526
PU	1 Stk

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.