

DOT CR 1W 3H NM AT

DETAILED CARD



TECHNICAL PARAMETERS

Index:	550683
Ingress protection:	IP65/20
Luminous flux [lm]*:	130
Colour temperature [K]:	5000
Material of the body:	PC
Emergency lighting [h]:	3
Battery:	NiMh
Operating mode:	NM
Autotest:	yes
Mounting version:	recessed

CHARACTERISTICS

Recessed mounted autonomous emergency luminaire with integrated, energy-saving LED module. Body made of polycarbonate (PC). Optical system available in 3 variants: basic, corridor, open space. Luminaire is fitted with batteries with 1h, 2h or 3h emergency operation time. The luminaire is using Ni-Mh or Ni-Cd battery with voltage of 3.6V and 24 hours of full charge with manual or automatic test function (AT).

APPLICATION

Emergency luminaire, used mainly for illumination of escape routes and fire protection devices after power failure, i.e. in emergency lighting mode. Depending on the optical system used, the luminaire may illuminate: escape routes (in corridor light distribution mode) or be used as anti-panic lighting (in standard light distribution mode or open space light distribution mode). Open Space light distribution mode is dedicated to openoffice space of lesser height.

DOT CR 1W 3H NM AT

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	1	Diffuser material:	PMMA
Index:	550683	Material of the body:	PC
Colour temperature [K]:	5000	Colour of the body:	white
EAN:	5905963550683	Dimensions (H/W/T/S) [mm]:	ø135/30
Luminous flux [lm]:	130	Mounting dimensions [mm]:	ø100
Light source:	LED module	Ingress protection:	IP65/20
Emergency lighting [h]:	3	Mounting version:	recessed
Rated power of the luminaire [W]:	1	Working temperature [°C]:	from +5 to +35
Light distribution type:	general	Net weight [kg]:	0.430
Operating mode:	NM	Category type:	emergency lighting
Supply voltage [V]:	220-240	Version:	general
Autotest:	yes	ETIM class:	EC001957
Frequency [Hz]:	50 - 60	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Luminous efficacy [lm/W]:	134	Luminaire rated power Omin [W]:	1
Electrical protection class:	I	Warranty [years]:	2 / 0.5 (bateria)
Energy efficiency class:	D	Warranty [years]:	2 / 0.5 (battery)
Colour rendering index:	>70	CE certificate:	77/2023
LED lifespan L70B50 [h]:	275000	Manual:	Download PDF
Beam angle [°]:	120	Plik LDT:	Download
Battery:	NiMh		

LIGHT CURVES

