




Highbay luminaires
4051859729617
D 570, H 509

Ceiling mounting, Suspension cable/chain,
Wall (surface)
deep black, matt (RAL 9005)



Round highbay luminaire for chain or cable suspension. Robust housing made of die-cast aluminium with eye ring, powder coated. Vertical cooling ribs ensure constant heat dissipation for optimal thermal management. Diffuser made of clear, non-reflecting, single pane safety glass (toughened glass). Refractor: PMMA, transparent. Primary light control with high-performance wide-area LEDs and reflector made of plastic (PMMA) for optimum glare limitation: UGR ≤ 19 . Easy to install thanks to 1-point suspension. Suitable for chain or steel cable suspension (to be provided on site). With power cord (1.5 m). Ceiling- and wall-mounting bracket available as accessory. Luminaire with limited surface temperature in accordance with EN 60598-2-24 for use in environments in which a deposit of conductive dust on the luminaire can be expected. Qualified for use in the food and drink industry.


Product specifications

Diameter D	570 mm
Height H	509 mm
Weight	5.28 kg
Light source	LED
Colour temperature	4000 K
Rated luminous flux	21500 lm
System power	165 W
System efficiency	130 lm/W
Glare evaluation UGR (4H 8H)	15
Beam angle	down 69° up 152°
Rated life	50000 h (L80/B10)
Colour rendering index (CRI)	80
Colour tolerance	5
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter
Control	on/off
Voltage	230 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	2
Luminaires on B16A fuse	4
Luminaires on C10A fuse	4
Luminaires on C16A fuse	7
Inrush current / Inrush current duration	75 A / 200 μ s
CIE Flux Code / CEN Flux Code	88 97 99 94 100
Type of protection	IP 65
Protection class	I
Filament test	650°C - 30 seconds
Impact resistance	IK03
Ambient temperature	-30 °C ... + 50 °C
Safety marks	D-mark
Conformity mark	CE


Accessories



982817.003
Ceiling and wall mounting bracket



982114.004
Reflector: aluminium



982115.000
Refractor: plastic