



CorePro GLASS LED candles and lusters

CorePro LEDLusterND6.5-60W P45 E27840FRG

Featuring a classic heritage design, these filament LED candle combines the familiar shapes of classic incandescent bulbs with the benefits of long-lasting LED technology. The LED candle bulb, a very easy choice for people who are looking for a retrofit LED replacement, the LED candle provides 90% energy savings compared with conventional lamps. CorePro Glass LED bulbs provide excellent quality of light for stairway lighting. The LED candle bulb offers a lifetime of 15,000 hours to reduce maintenance costs.

Product data

General Information		Operating and Electrical	
Cap-Base	E27	Line Frequency	50 to 60 Hz
Nominal lifetime	15,000 hour(s)	Input Frequency	50 to 60 Hz
Switching Cycle	20,000	Power Consumption	6.5 W
Lighting Technology	LED	Lamp Current (Nom)	50 mA
Flux measurement reference	Sphere	Wattage Equivalent	60 W
Light Technical		Starting Time (Nom)	0.5 s
Color Code	840 [CCT of 4000K]	Warm-up time to 60% light	0.5 s
Luminous Flux	806 lm	Power Factor (Fraction)	0.55
Color Designation	Cool White (CW)	Voltage (Nom)	220-240 V
Correlated Color Temperature (Nom)	4000 K	Temperature	
Luminous Efficacy (rated) (Nom)	124.00 lm/W	T-Case Maximum (Nom)	55 °C
Color Consistency	<6	Controls and Dimming	
Color rendering index (CRI)	80	Dimmable	No
LLMF At End Of Nominal Lifetime (Nom)	70 %		
Photobiological safety according to EN 62471	RG1		

CorePro GLASS LED candles and lusters

Mechanical and Housing

Bulb Finish	Frosted
Bulb Shape	P45
Net Weight (Piece)	0.014 kg

Approval and Application

Energy Efficiency Class	E
Energy Consumption kWh/1000 h	7 kWh
EPREL Registration Number	1825193
CE mark	Yes
EU RoHS compliant	Yes
EyeComfort	Yes
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	0.9


Application Conditions

can it be used in closed luminaires	No
-------------------------------------	----

Product Data



Order product name	CorePro LEDLusterND6.5-60W P45 E27840FRG
Full product name	CorePro LEDLusterND6.5-60W P45 E27840FRG
Full product code	871951434770000
Order code	929002029392
Material Nr. (12NC)	929002029392
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514347700
Numerator - Packs per outer box	10
EAN/UPC - Case	8719514347717

Dimensional drawing



Product	D	C
CorePro LEDLusterND6.5-60W P45 E27840FRG	45 mm	78 mm

Photometric data




General uniform lighting - CorePro LEDLusterND6.5-60W P45 E27840FRG

Spectral Power Distribution Colour - CorePro LEDLusterND6.5-60W P45 E27840FRG

CorePro GLASS LED candles and lusters

Photometric data




Light Distribution Diagram - CorePro LEDLusterND6.5-60W P45 E27840FRG

Lifetime



Lumen Maintenance Diagram - CorePro LEDLusterND6.5-60W P45 E27840FRG



Life Expectancy Diagram

