

SQ 300 LED PLUS LENS 2250 LM 830 IP54 II KL. DALI RCR AW3H AT OPAL (25W) 300MM CORRIDOR

DETAILED CARD



TECHNICAL PARAMETERS

Index:	665745
Ingress protection:	IP54
Impact resistance:	IK08
Nominal power [W]:	25
Luminous flux [lm]*:	2250
Colour temperature [K]:	3000
SDCM:	≤ 3
Energy efficiency class:	F
Material of the body:	ABS

CHARACTERISTICS

SQ 300 LED AW is a new line of square ceiling lamps. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, thanks to which it is characterized by low weight and high impact resistance (IK08). The diffuser made of PC polycarbonate provides the lamp with excellent lighting properties. Integrated LED module provides low power consumption and all the advantages of modern lamps with an LED source. The PLUS version of the luminaire line is equipped with brand components from recognized global manufacturers. It is characterized by extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

APPLICATION

The surface-mounted lamp for ceiling or wall mounting is intended for both indoor use - in rooms with high humidity, passageways, staircases, and outdoor use as façade lighting.


SQ 300 LED PLUS LENS 2250 LM 830 IP54 II KL. DALI RCR AW3H AT OPAL (25W) 300MM CORRIDOR

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	25	Impact resistance:	IK08
Index:	665745	Ingress protection:	IP54
Colour temperature [K]:	3000	Glow wire test [°C]:	650
EAN:	5905963665745	Mounting version:	surface
Luminous flux [lm]:	2250	Working temperature [°C]:	from -20 to +35
Emergency luminous flux [lm]*:	145	Corridor function:	yes
Diffuser type:	OPAL	Motion sensor:	yes
Supply voltage [V]:	220 - 240	Emergency lighting [h]:	3
Frequency [Hz]:	50 - 60	DIMM DALI:	yes
Luminous efficacy [lm/W]:	78	Dimensions of single box [mm]:	305/305/60
Energy efficiency class:	F	Number on the palette [pcs]:	120
Electrical protection class:	II	Net weight [kg]:	1.220
SDCM:	≤ 3	Category type:	bulkheads
Power factor:	0.92	Category of application:	HoReCa, commercial facilities, educational institutions
Charging time [h:min]:	48	Version:	LENS
Battery life [h:min]:	3	AC voltage range [V]:	176 - 280
Max load (RCR) [W]:	400	LED lifespan L70B50 [h]:	120000
Beam angle [°]:	120	LED lifespan L80B20 [h]:	80000
Battery:	NiMh	LED lifespan L90B10 [h]:	40000
Surge protection [kV]:	1	Light distribution type:	open space
Diffuser material:	PS	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Diffuser colour:	white	Technical Warranty:	2 / 0.5 (battery)
Optics material:	PMMA	CE certificate:	111/2023
Optics:	lens	ENEC Certificate:	0316/ENEC/23
Colour of the body:	white	PZH certificate:	B-BK-60212-0479/21
Material of the body:	ABS	CNBOP certificate:	5152/2023
Dimensions (H/W/T/S) [mm]:	300/300/58	Manual:	Download PDF
Mounting dimensions [mm]:	210		

LIGHT CURVES



SQ 300 LED PLUS LENS 2250 LM 830 IP54 II KL. DALI RCR AW3H AT OPAL (25W) 300MM CORRIDOR

DETAILED CARD

Card creation date: 09 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric andelectronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 111/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl