

S.GROUND

LED SPIKE

STL23756/30



18,5W

Power

1500lm

Luminous flux

36°

Beam angle




TECHNICAL SPECIFICATIONS TABLE

Beam angle	36°
Luminous efficacy	81lm/W
Power factor	0,92
Luminous flux	1500lm
Frequency	50/60Hz
Ingress protection rating (IP)	IP67
CRI (Color rendering index)	80
Luminous intensity	3800cd
Power	18,5W
Correlated color temperature (CCT)	3000K
Voltage (V)	100-240V
Voltage (Vac)	100-240Vac
Lifespan	25000h

Technical Drawing

STL23756




Graphics

STL23756

1m	3964lx	0,7m
2m	991lx	1,5m
3m	440lx	2,2m
4m	248lx	2,9m
5m	159lx	3,6m

h, Emax, Ø

STL23756



— C0/80 — C90/270

OTHER INFORMATION

Finishing	Black
Color temperature	Warm white
Dimmable	No
Warranty	2 years
Patent information	Patented product
Prevailing material	Aluminum

DOWNLOADS

↓ IES FILE - STL23756/30

↓ MANUAL S.Ground

↓ SKETCHUP - STELLA - STL23756-30 - ESPETO GROUND 20W
SEM GRADE_PACK.zip

↓ REVIT - STL23756_30.rfa

