



# TRIXY square

901722.002 | Surface mounted downlights



Surface mounted downlights, Recessed downlights  
4051859768913  
L 235, B 235, H 22

Ceiling mounting, Recessed ceiling mounting, Wall (surface)  
white



Ultra-flat square downlight suitable for recessed or surface installation. Housing made of UV-resistant polycarbonate. Perfect heat management with an aluminium heat sink. Diffuser: plastic (PMMA), transparent, with opal reflector foil. Lateral light emission (RZB SIDELITE® technology) for homogeneous light distribution. MultiColour: With rear switching element, variable colour temperature 3000 K or 4000 K. Factory setting is 4000 K. MultiLumen: 3 steps adjustable luminous flux. Factory setting is the highest luminous flux. MultiCutOut: With adjustable spring clamps, different ceiling cut-outs can be individually adhered to. Suitable for ceiling cut-outs from Ø 65 to 205 mm. Suitable for recessed mounting in ceilings and surface mounting on ceilings and walls. Suitable for through-wiring. Driver integrated.

# TRIXY square

## 901722.002 | Surface mounted downlights



### Product specifications

Length L	235 mm
Width B	235 mm
Height H	22 mm
Cut-out diameter DA	65-205 mm
Luminaire: recess height HEL	25 mm
Ceiling thickness S	5-25 mm
Installation space height HE	82 mm
Weight	460 g
Light source	LED
Colour temperature	3000 K   4000 K
Rated luminous flux	3000 K: 990 lm   1500 lm
	4000 K: 1050 lm   1700 lm
System power	3000 K: 9 W   15 W
	4000 K: 9 W   15 W
System efficiency	3000 K: 110 lm/W   100 lm/W
	4000 K: 117 lm/W   113 lm/W
Glare evaluation UGR (4H 8H)	3000 K: 24,3   25,8
	4000 K: 24,5   26,2
Beam angle	114°
Rated life	40000 h (L70/B50)
Colour rendering index (CRI)	80
Colour tolerance	4
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter
Control	on/off
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	37
Luminaires on B16A fuse	59
Luminaires on C10A fuse	37
Luminaires on C16A fuse	59
Inrush current / Inrush current duration	2.46 A / 51 µs
CIE Flux Code / CEN Flux Code	47 78 95 100 100
Type of protection	IP 20
Protection class	II
Filament test	650 °C
Impact resistance	IK02
Ambient temperature	-20 °C ... + 40 °C
Conformity mark	CE, EAC, UKCA

### Accessories



983110.012  
HF movement sensor in separate box.