



# HF-Selectalume II for TL5 lamps

## HF-S 254 TL5 II 220-240V 50/60Hz

HF-Selectalume II TL5 is the most cost-effective, reliable and outstanding solution for fluorescent lamps. These ballasts are part of an overall high-efficiency lighting system that may help you or your customers to achieve any international or local energy code you need to comply with. HF-Selectalume II TL5 ballasts are the ideal choice for a broad range of new construction and retrofit applications within the commercial sector, including general surface mounting or office lighting, parking garages, warehouses, waterproof and other applications. The ballast is primarily designed for Indoor application. For outdoor application, the luminaire should be minimum Classland need to be sufficiently protected against water & dust. The installation should also be guard against any lightening surge or any other necessary electrical protection as deemed in such typical installation & application.

### Product data

General Information	
Number of Lamps	2 piece/unit

  

Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Earth Leakage Current (Max)	0.5 mA
Inrush Current Width	0.38 ms
Inrush Current Peak (Max)	28 A

  

Temperature	
Ambient temperature range	-15 °C to 50 °C
T-Case Lifetime (Nom)	75 °C
T-Case Maximum (Max)	75 °C

  

Mechanical and Housing	
Housing	L 280x30x21

  

Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Energy Efficiency Index	A2 BAT

  

Wiring	
Connector Type Input Terminals	WAGO 744 connector

  

Connector Type Output Terminals	
WAGO 744 connector [Suitable for manual wiring]	

## HF-Selectalume II for TL5 lamps

<b>Approval Marks</b>	F-Marking CE marking ENEC certificate CCC certificate C-Tick certificate PSB certification TISI marking SIRIM approval CB Certificate CCC certificate VDE-EMV certificate
-----------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### Product Data

<b>Full product code</b>	872790090562500
<b>Order product name</b>	HF-S 254 TL5 II 220-240V 50/60Hz
<b>Order code</b>	913713033766

<b>Numerator - Quantity Per Pack</b>	1
<b>Numerator - Packs per outer box</b>	12
<b>Material number (12NC)</b>	913713033766
<b>Full product name</b>	HF-S 254 TL5 II 220-240V 50/60Hz
<b>EAN/UPC - Case</b>	8727900905625



## Dimensional drawing

A2

Product	D1	C1	A1	A2	B1
HF-S 254 TL5 II 220-240V 50/60Hz	4.1 mm	21.5 mm	360.0 mm	350.0 mm	30.0 mm

