ANDHO mini


722277.0031.2 | Garden spotlights





Garden spotlights 4051859922704 L 397, B 114, H 210

Earth pike anthracite metallic (DB703)



Powerful LED garden spot with peg. Housing: die-cast aluminium, seawater resistant powder-coated. Integral membrane valve for pressure compensation and avoidance of condensation. Reflector made of super-reflective MIRO-SILVER® for outstanding efficiency. Cover clear single-pane toughened glass, edge printed. Light distribution medium, medium-wide beam. Peg made of fiber reinforced plastic. Driver integrated. With 5 m power supply cable, including safety plug.

Product specifications

i roduct specifications		
Length L	397 mm	
Width B	114 mm	
Height H	210 mm	
Weight	2.3 kg	
Light source	LED	
Colour temperature	2700 K	
Rated luminous flux	1450 lm	
System power	13 W	
System efficiency	112 lm/W	
Glare evaluation UGR (4H 8H)	15,4	
Beam angle	26°	
Rated life	50000 h (L80/B10)	
Colour rendering index (CRI)	80	
Colour tolerance	2	
Photobiological safety according to EN 62471	Risk group 1	
Driver	Converter	
Control	on/off	
Voltage	220 - 240 V / 50 Hz, 60 Hz	
Luminaires on B10A fuse	17	
Luminaires on B16A fuse	27	
Luminaires on C10A fuse	28	
Luminaires on C16A fuse	46	
Inrush current / Inrush current duration	27 A / 250 μs	
CIE Flux Code / CEN Flux Code	97 100 100 100 100	
Type of protection	IP 65	
Protection class		
Filament test	960 °C	
Impact resistance	IK07	
Ambient temperature	-20 °C + 35 °C	
Safety marks	Do not cover the recessed luminaire!	
Conformity mark	CE	

ANDHO mini

722277.0031.2 | Garden spotlights



Accessories



982159.000 Reeded glass



982168.003 Barn door shutter



982165.003 Snap-on hood



982162.003 Louvres