




Pendant luminaires
4051859232957
L 1512, B 28, H 38

pendant
traffic white, matt (RAL 9016)



Pendant luminaire with slim design. Housing: extruded aluminium profile, powder-coated. End cap aluminium powder-coated. Diffuser made of non-yellowing plastic (PMMA) microprismatic. Direct 60%, indirect 40% light emission. Suitable for pendant. 2-point steel cable suspension, steplessly adjustable. Special lengths available on request. Converter integrated in the canopy.

Product specifications

Length L	1512 mm
Width B	28 mm
Height H	38 mm
Suspension length LP	100-1500 mm
Weight	2.14 kg
Light source	LED
Colour temperature	#4000 K #4000 K
Rated luminous flux	4500 lm
System power	51 W
System efficiency	88 lm/W
Glare evaluation UGR (4H 8H)	22,4
Beam angle	down 64°/86° up 75°/101°
Rated life	60000 h (L80/B10)
Colour rendering index (CRI)	82
Colour tolerance	3
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter
Control	on/off
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	11
Luminaires on B16A fuse	18
Luminaires on C10A fuse	19
Luminaires on C16A fuse	31
Inrush current / Inrush current duration	24 A / 275 µs
CIE Flux Code / CEN Flux Code	66 89 98 70 100
Type of protection	IP 20
Protection class	I
Filament test	650 °C
Impact resistance	IK00
Ambient temperature	-25 °C ... + 25 °C
Conformity mark	CE, EAC