



MASTER PL-L Xtra 4 Pin

MASTER PL-L XTRA 24W/840/4P 1CT/25

MASTER PL-L Xtra is a medium to high-wattage linear compact fluorescent lamp, typically used for general-illumination ceiling luminaires in retail, hospitality and office applications demanding higher lighting levels. MASTER PL-L Xtra lamps furthermore provide significantly lower operating costs thanks to their lifetime, which is more than double that of a standard MASTER PL-L lamp, and their very low early failure rate. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. It is designed for operation on electromagnetic as well as HF electronic gear and is provided with a plug-in/pull-out lamp base.

Warnings and Safety

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied control gear
- Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information		Chromaticity Coordinate X (Nom)		0.38
Cap-Base	2G11 [2G11]	Chromaticity Coordinate Y (Nom)		0.38
Flux measurement reference	Sphere	Correlated Color Temperature (Nom)		4000 K
Light Technical		Luminous Efficacy (rated) (Nom)		75 lm/W
Color Code	840 [CCT of 4000K]	Color rendering index (CRI)		80
Luminous Flux	1,800 lumen	Operating and Electrical		
Color Designation	Cool White (CW)	Power Consumption	24.3 W	

MASTER PL-L Xtra 4 Pin


Lamp Current (Nom)	0.345 A
Controls and Dimming	
Dimmable	Yes
Approval and Application	
Mercury (Hg) Content (Max)	3 mg
Mercury (Hg) Content (Nom)	3.0 mg
Energy Consumption kWh/1000 h	25 kWh
EPREL Registration Number	423,308

Product Data	
Full product code	871150026770240
Order product name	MASTER PL-L XTRA 24W/840/4P 1CT/25
Order code	927907584015
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material number (12NC)	927907584015
Full product name	MASTER PL-L XTRA 24W/840/4P 1CT/25
EAN/UPC - Case	8711500267719

Dimensional drawing

Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-L XTRA 24W/840/4P 1CT/25	39.0 mm	18.0 mm	290 mm	315 mm	321.6 mm

Photometric data



Spectral Power Distribution Colour - MASTER PL-L XTRA 24W/840/4P 1CT/25

MASTER PL-L Xtra 4 Pin

