

# TYTAN 2 LED ENDURA MINUS 1150MM 9050LM 840 IP66 55W

DETAILED CARD



## TECHNICAL PARAMETERS

|                          |        |
|--------------------------|--------|
| Index:                   | 911507 |
| Ingress protection:      | IP66   |
| Impact resistance:       | IK09   |
| Nominal power [W]:       | 55     |
| Luminous flux [lm]*:     | 9050   |
| Colour temperature [K]:  | 4000   |
| Energy efficiency class: | C      |
| Material of the body:    | PC     |
| Colour of the body:      | grey   |
| Diffuser material:       | PC     |

## CHARACTERISTICS

TYTAN 2 LED ENDURA is a fitting from NEXT GEN line, which is a new generation of fittings in LED technology. The fitting, designed from scratch, allows new solutions improving the light distribution and temperature balance. Branded led diodes and new LED modules have influence on a very high luminous flux: 155 lm/W. It guarantees the best required lighting level and energy saving up to 68%. The solution based on integration of the diffuser and LED modul is applied in the fitting. The fitting has a lot of facilities making the mounting easier and faster: the system of diffuser suspension, adjustable mounting brackets ensuring the mounting tolerance +/-50mm. Standard equipment of the fitting: clips made of stainless steel (INOX). The body of the fixture and the diffuser are resistant to UV radiation.

## APPLICATION

The multifunctional LED lamp is designed for use in areas with high requirements for dust and water resistance. Especially recommended for lighting public facilities, including hospitals, educational facilities, halls, garages, passages, warehouses, shops, food industry, commercial and industrial facilities (factories, laboratories), warehouses, parking lots (underground and multi-level), sports stadiums, transport terminals and underground passages. The luminaire is ideal for new lighting applications as well as replacing traditional fluorescent luminaires with energy-saving LED solutions. Its design is adapted for surface and suspended mounting.


# TYTAN 2 LED ENDURA MINUS 1150MM 9050LM 840 IP66 55W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                                   |                 |                           |                                          |
|-----------------------------------|-----------------|---------------------------|------------------------------------------|
| Nominal power [W]:                | 55              | Impact resistance:        | IK09                                     |
| Index:                            | 911507          | Ingress protection:       | IP66                                     |
| Light source:                     | LED module      | Mounting version:         | surface, suspended                       |
| Colour temperature [K]:           | 4000            | Net weight [kg]:          | 1                                        |
| Luminous flux [lm]:               | 9050            | Category type:            | battens                                  |
| Rated power of the luminaire [W]: | 59.30           | Category of application:  | industrial                               |
| Diffuser type:                    | MAT             | LED lifespan L70B50 [h]:  | 85000                                    |
| Supply voltage [V]:               | 220 - 240       | LED lifespan L80B20 [h]:  | 54000                                    |
| Frequency [Hz]:                   | 50 - 60         | LED lifespan L90B10 [h]:  | 26000                                    |
| Working temperature [°C]:         | from -40 to +45 | Photobiological safety:   | RG0 - exempt (no photobiological hazard) |
| Luminous efficacy [lm/W]:         | 153             | Exchangeable source:      | yes                                      |
| Dimensions (H/W/T/S) [mm]:        | 1152/85/80      | Surge protection [kV]:    | 4                                        |
| Energy efficiency class:          | C               | Mounting dimensions [mm]: | 800                                      |
| Electrical protection class:      | I               | Version:                  | MINUS                                    |
| Colour rendering index:           | >80             | Warranty [years]:         | 5                                        |
| SDCM:                             | ≤ 3             | CE certificate:           | <a href="#">130/2023</a>                 |
| Power factor:                     | 0.95            | PZH certificate:          | <a href="#">B-BK-60212-0152/20</a>       |
| Diffuser material:                | PC              | HACCP:                    | <a href="#">852/2004</a>                 |
| Material of the body:             | PC              | ENEC Certificate:         | <a href="#">0310/ENEC/23</a>             |
| Colour of the body:               | grey            | Manual:                   | <a href="#">Download PDF</a>             |
|                                   |                 | ETIM class:               | EC000109                                 |
|                                   |                 | Plik LDT:                 | <a href="#">Download</a>                 |

## LIGHT CURVES



# TYTAN 2 LED ENDURA MINUS 1150MM 9050LM 840 IP66 55W

DETAILED CARD

## TECHNICAL DETAILS



regulowane uchwyty / adjustable  
handles / einstellbare Halterungen



system zwieszania klosza / suspension  
system of the diffuser / hängende  
Diffusor




wybór miejsca zasilania / choosing a  
place of power supply /  
Stromversorgungsanschluss von  
mehreren Seite möglich

# TYTAN 2 LED ENDURA MINUS 1150MM 9050LM 840 IP66 55W

DETAILED CARD

## ACCESSORIES AVAILABLE

| index    | Name                                                              |
|----------|-------------------------------------------------------------------|
| 908200   | TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) |
| 60000006 | M16 stuffing box plug various PA black M-16 - BPM-21              |
| 80000279 | Gland. beam, Codar, soft polyvinyl chloride (PVC-P), gray         |



TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) (908200)



M16 stuffing box plug various PA black M-16 - BPM-21 (60000006)

Card creation date: 08 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 130/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl