

CAPELLA LED PLUS EDGE BOX 1500LM 840 IP54 DALI BIAŁY (15W) 320MM

DETAILED CARD



TECHNICAL PARAMETERS

Index:	949456
Ingress protection:	IP54
Impact resistance:	IK06
Nominal power [W]:	15
Luminous flux [lm]*:	1500
Colour temperature [K]:	4000
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	ABS

CHARACTERISTICS

CAPELLA LED is a wide line of luminaires combining high aesthetic values and lighting parameters. The body has been made from ABS and the frosted diffuser from impact-resistant polycarbonate (PC). A multitude of versions makes it possible to adapt the luminaire to many non-standard applications.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

This ceiling fixture is also available in the following variants:

- with a radio motion sensor,
- with a PIR presence detector,
- with DALI control,
- with CORRIDOR function (DALI + RCR),
- with Master / Slave RCR motion sensor (wireless),
- with emergency module,
- with very high ingress protection IP65,
- with ANTIVANDAL protection.

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes). It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

CAPELLA LED PLUS EDGE BOX 1500LM 840 IP54 DALI BIAŁY (15W) 320MM

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	15	Diffuser type:	OPAL
Light source:	LED module	Diffuser colour:	white
Colour temperature [K]:	4000	Optics material:	PMMA
Luminous flux [lm]:	1500	Optics:	lens
Rated power of the luminaire [W]:	16	Material of the body:	ABS
Supply voltage [V]:	220-240	Colour of the body:	white
Frequency [Hz]:	50 - 60	Mounting dimensions [mm]:	158
EDGE/BOX Colour:	white	Impact resistance:	IK06
Version:	EDGE BOX	Ingress protection:	IP54
Luminous efficacy [lm/W]:	94	Mounting version:	surface
Energy efficiency class:	E	Working temperature [°C]:	from -10 to +35
Electrical protection class:	II	Accessories included:	gland, extraction, 2x cover cable, screws, wall plugs 6mm
Colour rendering index:	>80	Dimensions of single box [mm]:	342/342/122
DIMM DALI:	yes	Net weight [kg]:	0.870
SDCM:	≤ 3	Warranty [years]:	5
Power factor:	0.94	CE certificate:	373/2023
Dimensions (H/W/T/S) [mm]:	320/105	Index:	949456
LED lifespan L70B50 [h]:	115000	EAN:	5905963949456
Beam angle [°]:	120	Category type:	bulkheads
Surge protection [kV]:	1	Product line:	plus
Diffuser material:	PC	AC voltage range [V]:	220 - 240
		UGR (4H8H):	17,5-25,2
		Light distribution type:	lambertian
		Dimensions of bulk box (H/W/D) [mm]:	794/1194/982
		Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
		Manual:	Download PDF
		Plik LDT:	Download

LIGHT CURVES

