



# MASTER - LED HID SON-T - Ultra Efficient



## MAS LED SON-T UE M 5.4Klm 28.5W 727 E27

Philips MASTER - LED HID SON-T Ultra Efficient lamps are an easy LED solution with the highest efficiency to replace High-Intensity Discharge (HID) and High-Pressure Sodium (SON) lamps. MASTER - LED HID SON-T UE solutions bring the energy efficiency and long lifetime benefits of LED to HID replacement, providing instant savings for low energy costs. With the right lamp size and light distribution, you can easily use MASTER - LED HID SON-T UE lamps into existing SON and SON-T systems, enhancing the lighting quality with LED by removing the luminaire's ballast for direct Mains working, gaining additional savings.

### Warnings and Safety

- Installation should always be performed by a qualified electrician or installer. Use the installation guide for instructions.

### Product data

General Information			
Cap-Base	E27	Luminous Flux	5,400 lm
Nominal lifetime	50,000 hour(s)	Color Designation	Warm White (WW)
Switching Cycle	50,000	Correlated Color Temperature (Nom)	2700 K
Lighting Technology	LED	Luminous Efficacy (rated) (Nom)	189 lm/W
Flux measurement reference	Sphere	Color Consistency	<6
Value ladder	Performance	Color rendering index (CRI)	70
Light Technical		LLMF At End Of Nominal Lifetime (Nom)	70 %
Color Code	727 [CCT of 2700K]	Photobiological safety according to EN 62471	RG1
Beam Angle (Nom)	300 degree(s)	Operating and Electrical	
		Input Frequency	50 to 60 Hz

MASTER - LED HID SON-T - Ultra Efficient

Power Consumption	28.5 W
Lamp Current (Nom)	130 mA
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	220-240 V
Inrush current at mains	24.6
Max. lamp no. on MCB B type 10A - Mains	8
Max. lamp no. on MCB B type 10A – EM ballast without Compensation Capacitor.	-
Max. lamp no. on MCB B type 10A – EM ballast with Compensation Capacitor.	-
Max. lamp no. on MCB B type 16A - Mains	14
Max. lamp no. on MCB B type 16A – EM ballast without Compensation Capacitor.	-
Max. lamp no. on MCB B type 16A – EM ballast with Compensation Capacitor.	-
Ballast Compatibility	Mains

Temperature

T-Case Maximum (Nom)	48.21 °C
----------------------	----------

Controls and Dimming

Dimmable	No
----------	----

Mechanical and Housing

Bulb Finish	Clear
Bulb Shape	T46
Net Weight (Piece)	0.122 kg

Approval and Application

Energy Efficiency Class	B
Energy Consumption kWh/1000 h	29 kWh
EPREL Registration Number	2096241
CE mark	Yes
EU RoHS compliant	Yes
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	2
Ambient temperature range	-30 to +45 °C


Application Conditions

can it be used in closed luminaires	Yes
-------------------------------------	-----

Product Data

Order product name	MAS LED SON-T UE M 5.4Klm 28.5W 727 E27
Full product name	MAS LED SON-T UE M 5.4Klm 28.5W 727 E27
Full product code	872016937423200
Order code	929003677332
Material Nr. (12NC)	929003677332
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169374232
Numerator - Packs per outer box	6
EAN/UPC - Case	8720169374249


Dimensional drawing




Product	D	C
MAS LED SON-T UE M 5.4Klm 28.5W 727 E27	47 mm	194 mm

MASTER - LED HID SON-T - Ultra Efficient


Photometric data



General uniform lighting - MAS LED SON-T UE M 5.4Klm 28.5W 727 E27




Spectral Power Distribution Colour - MAS LED SON-T UE M 5.4Klm 28.5W 727 E27




Light Distribution Diagram - MAS LED SON-T UE M 5.4Klm 28.5W 727 E27

Lifetime



Life Expectancy Diagram



Lumen Maintenance Diagram - MAS LED SON-T UE M 5.4Klm 28.5W 727 E27

## MASTER - LED HID SON-T - Ultra Efficient

