



Corepro LED Strip



CorePro LEDstrip 6W840 800LM/M 5M

A complete family that are bright, slim, safe & reliable. Choose the best fit for every projects, from 4 lumen packs/wattages, and 4 CCTs, and enjoy easy installation with slimness

Product data

| General Information | |
|--|--------------------------|
| Driver included | No |
| Lighting Technology | LED |
| Warranty period | 3 years |
| | |
| Light Technical | |
| Luminous Flux | 800 lm |
| Correlated Color Temperature (Nom) | 4000 K |
| Luminous Efficacy (rated) (Nom) | 133.00 lm/W |
| Color rendering index (CRI) | 80 |
| Photobiological safety according to EN 62471 | RG1 |
| | |
| Operating and Electrical | |
| Input Voltage | 24 V |
| Initial CLO power consumption | 27 W |
| Average CLO power consumption | 0 W |
| Power Consumption | 27 W |
| Power Factor (Fraction) | 1 |
| Cable | Cable 0.3 m without plug |
| Number of products on MCB of 16 A type B | - |
| Protection class IEC | Safety class III |
| | |
| Controls and Dimming | |
| Dimmable | Yes |
| | |

| Control interface | depends on driver (1-10V, DALI) |
|-------------------------------------|-----------------------------------|
| Constant light output | No |
| Maximum dim level | 10% (depends on dimmer, ELV) |
| | |
| Mechanical and Housing | |
| Reflector material | - |
| Overall length | 5,000 mm |
| Overall width | 8 mm |
| Overall height | 1.3 mm |
| Dimensions (Height x Width x Depth) | 1 x 8 x 5000 mm |
| Ingress protection code | IP20 [Finger-protected] |
| Mech. impact protection code | IK00 [No protection] |
| Net Weight (Piece) | 0.100 kg |
| | |
| Approval and Application | |
| Energy Efficiency Class | E |
| EPREL Registration Number | 620710 |
| Glow-wire test | Temperature 650 °C, duration 30 s |
| CE mark | Yes |
| EU RoHS compliant | Yes |
| Ambient temperature range | -20 to +40 °C |
| · | |
| Initial Performance (IEC Compliant) | <u> </u> |
| Luminous flux tolerance | +/-10% |

Datasheet, 2025, March 11 data subject to change

Corepro LED Strip


| (0.3818, 0.3797) 5SDCM | | |
|---------------------------------------|--|--|
| +/-10% | | |
| | | |
| Over Time Performance (IEC Compliant) | | |
| 35,000 hour(s) | | |
| | | |
| | | |
| CorePro LEDstrip 6W840 800LM/M 5M | | |
| CorePro LEDstrip 6W840 800LM/M 5M | | |
| | | |

| Full product code | 871951434412900 |
|---------------------------------|-----------------|
| Order code | 929002695302 |
| Material Nr. (12NC) | 929002695302 |
| Numerator - Quantity Per Pack | 1 |
| EAN/UPC - Product/Case | 8719514344129 |
| Numerator - Packs per outer box | 10 |
| EAN/UPC - Case | 8719514344136 |
| | |


Dimensional drawing



Photometric data



Light Distribution Diagram - CorePro LEDstrip 6W840 800LM/M 5M



Calculus Processes (1.1) Philips Lighting B.Y. Page 197

General uniform lighting - CorePro LEDstrip 6W840 800LM/M 5M



© 2025 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.