



# Capsules LV 3000 h

## Caps 3000h 14.3W G4 12V CL 1CT/10x10F

Low-voltage halogen capsule. Ideal solution for small decorative luminaires. UV-block glass and low-pressure filling allow usage without cover glass. The compact halogen capsule delivers crisp white light over a long lifetime.

#### **Product data**

General Information			
Cap-Base	G4 [G4]		
Operating Position	UNIVERSAL [Any or Universal (U)]		
Nominal lifetime	3,000 hour(s)		
Switching Cycle	12,000		
Rated Lifetime (Hours)	3,000 hour(s)		
Lighting Technology	Halogen		
Light Technical			
Luminous Flux	232 lumen		
Correlated Color Temperature (Nom)	2900 K		
Luminous Efficacy (rated) (Nom)	16.6 lm/W		
Color rendering index (CRI)	100		
Operating and Electrical			
Power Consumption	14.0 W		
Lamp Current (Nom)	1.167 A		
Starting Time (Nom)	0.0 s		
Warm-up time to 60% light	Instant full light s		
Power Factor (Fraction)	1		
Voltage (Nom)	12 V		
Voltage (Nom)	12 V		

Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	T9 [T 9mm (T9)]
Approval and Application	
Energy Consumption kWh/1000 h	14 kWh
Product Data	
Full product code	871869682774100
Order product name	Caps 3000h 14.3W G4 12V CL 1CT/10x10F
Order code	925723417102
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	100
Material number (12NC)	925723417102
Full product name	Caps 3000h 14.3W G4 12V CL 1CT/10x10F
EAN/UPC - Case	8718696827765

Datasheet, 2023, May 16 data subject to change

### Capsules LV 3000 h

#### Dimensional drawing



Product	D (max)	L	C (max)
Caps 3000h 14.3W G4 12V CL 1CT/10x10F	10 mm	22.2 mm	33 mm

