

S.GROUND

LED SPIKE

STL23752/30



3W

Power

250lm

Luminous flux

36°

Beam angle




TECHNICAL SPECIFICATIONS TABLE

Beam angle	36°
Luminous efficacy	83lm/W
Power factor	0,7
Luminous flux	250lm
Frequency	50/60Hz
Ingress protection rating (IP)	IP67
CRI (Color rendering index)	80
Luminous intensity	600cd
Power	3W
Correlated color temperature (CCT)	3000K
Voltage (V)	100-240V
Voltage (Vac)	100-240Vac
Lifespan	25000h

Technical Drawing

STL23752




Graphics

STL23752

1m	612lx	0,6m
2m	153lx	1,3m
3m	68lx	1,9m
4m	38lx	2,5m
5m	24lx	3,2m

h, Emax, ø

STL23752



OTHER INFORMATION

Finishing	Black
Color temperature	Warm white
Dimmable	No
Warranty	2 years
Patent information	Patented product
Prevailing material	Polycarbonate

DOWNLOADS

↓ IES FILE - STL23752/30

↓ MANUAL S.Ground

↓ SKETCHUP - STELLA - STL23752-30 - ESPETO GROUND 3W
SEM GRADE_PACK.zip

↓ REVIT - STL23752_30.rfa

