

TOLEDO FLAT+ square 901817.0031.2.76 | Recessed downlights





Recessed downlights 4051859933151 L 310, B 310, H 2

Recessed ceiling mounting anthracite metallic (DB703)



Flexible square recessed multifunction downlight. Housing: sheet steel, powder-coated. Luminaire frame: aluminium, powder-coated. Light guide and diffuser made of non-yellowing PMMA, opal matt. LED backlight technology for homogeneous illumination of the entire light-emitting surface. Tunable white dynamically adjustable from 2700 K to 6500 K. Suitable for Recessed ceiling mounting. Ceiling installation with spring system. Can be directly covered with thermal insulation material (applies only to the lower lumen levels). Including separate LED converter with connecting cable 250 mm.





Product specifications

Product specifications		
Length L	310 mm	
Width B	310 mm	
Height H	2 mm	
Cut-out length LA	297 mm	
Cut-out width BA	297 mm	
Luminaire: recess height HEL	42 mm	
Ceiling thickness S	1-20 mm	
Installation space length LE	500 mm	
Installation space width BE	410 mm	
Installation space height HE	60 mm	
Weight	1.13 kg	
Light source	LED	
Colour temperature	2700 - 6500 K	
Rated luminous flux	22502350 lm	
System power	1919 W	
System efficiency	118124 lm/W	
Beam angle	113°	
Rated life	50000 h (L80/B10)	
Colour rendering index (CRI)	80	
Colour tolerance	3	
Photobiological safety according to EN 62471	Risk group 1	
Driver	Converter, dimmable	
Control	DALI	
Voltage	220 - 240 V / 50 Hz, 60 Hz	
Luminaires on B10A fuse	18	
Luminaires on B16A fuse	30	
Luminaires on C10A fuse	31	
Luminaires on C16A fuse	51	
Inrush current / Inrush current duration	29 A / 153 μs	
CIE Flux Code / CEN Flux Code	47 79 96 100 100	
	IP 54 on room side	
Type of protection	IP 20	
Protection class	II	
Filament test	650 °C	
Impact resistance	IK03	
Ambient temperature	-20 °C + 35 °C	
Safety marks	Do not cover the recessed luminaire!	
Conformity mark	CE, EAC	

Accessories



982923.0031 Surface mounted housing



983083.0031 refurbishment frames for recessed luminaires