## DEECOS S mini track-in


### 742250.003.1.730 | Surface mounted projector





Surface mounted projectors 4051859811480 D 87, H 135

Track on ceiling, Wall track deep black, matt (RAL 9005)



LED surface-mounted projector in modern design with no visible cooling ribs. Housing: die-cast aluminium, powder-coated. Rotation range: 356°. Swivel range: 90°. Black plastic ring and recessed LED to prevent glare from the side. Optical assembly with reflector made of MIRO-Silver with 98% total light reflection for outstanding efficiency - can be changed without tools. Best colour rendering index Ra>90. With multi adaptor for 3-circuit tracks 230 V. Suitable for Track on ceiling, Wall track. Track-in driver integrated into the adapter. High quality converter without flickering and stroboscopic effect. With Casambi smart+free Bluetooth® control for wireless network and operation using Android / iOS devices, free app available for download. The following accessories can be mounted without use of tools: interchangeable lenses, decorative glasses, honeycomb louvre, clear and frosted diffusers, white interchangeable plastic ring.

#### **Product specifications**

Product specifications	
Diameter D	87 mm
Height H	135 mm
Weight	0.62 kg
Light source	LED
Colour temperature	4000 K
Rated luminous flux	2700 lm
System power	20 W
System efficiency	135 lm/W
Glare evaluation UGR (4H 8H)	14,2
Beam angle	18°
Rated life	50000 h (L90/B10)
Colour rendering index (CRI)	92
Colour tolerance	2
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter, dimmable
Control	smart+free (Bluetooth)
Voltage	220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse	17
Luminaires on B16A fuse	27
Luminaires on C10A fuse	28
Luminaires on C16A fuse	44
Inrush current / Inrush current duration	18 A / 2 μs
CIE Flux Code / CEN Flux Code	100 100 100 100 100
Type of protection	IP 20
Protection class	II
Filament test	650°C - 30 seconds
Impact resistance	IK06
Ambient temperature	25 ℃
Conformity mark	CE, EAC

# DEECOS S mini track-in

### 742250.003.1.730 | Surface mounted projector



#### **Accessories**



982370.000 Diffuser, transparent



982371.003 Anti-glare honeycomb louvre



982369.013 Medium lens



982421.002 White plastic ring for lens.



982368.013 Reflector medium



982369.033 Wide flood lens



982419.002 White plastic ring for reflector.



982647.002 Decorative glass opal matt



982370.010 Diffuser, satinated



982369.003 Spot lens



982369.023 Flood lens



982368.003 Reflector spot



982368.023 Reflector flood



982369.043 Oval corridor lens



982368.033 Reflector wide flood



982648.002 Decorative glass opal matt